

BUSATTI LINE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030100804001200	400X1200	8	59	355	56,5	99,5	43	15	30	1,28	C-E-D
5030100804001400	400X1400	10	59	355	56,5	99,5	43	15	30	1,40	C-E-D
5030100804001600	400X1600	12	59	355	56,5	99,5	43	15	30	1,51	C-E-D
5030100804001800	400X1800	14	59	355	56,5	99,5	43	15	30	1,62	C-E-D
5030100806001200	600X1200	10	59	555	56,5	99,5	43	15	30	1,70	C-E-D
5030100806001400	600X1400	12	59	555	56,5	99,5	43	15	30	1,82	C-E-D
5030100806001600	600X1600	14	59	555	56,5	99,5	43	15	30	1,93	C-E-D
5030100806001800	600X1800	16	59	555	56,5	99,5	43	15	30	2,04	C-E-D


HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030100804001200	377	1286	491	1675
5030100804001400	401	1368	522	1781
5030100804001600	428	1460	557	1900
5030100804001800	459	1566	597	2036
5030100806001200	572	1951	744	2538
5030100806001400	595	2029	774	2640
5030100806001600	623	2125	810	2763
5030100806001800	654	2231	851	2902

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7,24	9,21	0,06	432X1330X101
7,84	10,04	0,07	432X1530X101
8,44	10,86	0,08	432X1730X101
9,03	11,69	0,09	432X1930X101
9,99	12,49	0,09	632X1330X101
10,59	13,39	0,10	632X1530X101
11,19	14,29	0,12	632X1730X101
11,78	15,19	0,13	632X1930X101

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel