

DORE DOUBLE LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101004001200	400X1200	8	61	355	56,5	87	26	15	30	1,28	C-E-D
5030101004001400	400X1400	10	61	355	56,5	87	26	15	30	1,40	C-E-D
5030101004001600	400X1600	12	61	355	56,5	87	26	15	30	1,51	C-E-D
5030101004001800	400X1800	14	61	355	56,5	87	26	15	30	1,62	C-E-D
5030101005001200	500X1200	9	61	455	56,5	87	26	15	30	1,49	C-E-D
5030101005001400	500X1400	11	61	455	56,5	87	26	15	30	1,61	C-E-D
5030101005001600	500X1600	13	61	455	56,5	87	26	15	30	1,72	C-E-D
5030101005001800	500X1800	15	61	455	56,5	87	26	15	30	1,83	C-E-D
5030101006001200	600X1200	10	61	555	56,5	87	26	15	30	1,70	C-E-D
5030101006001400	600X1400	12	61	555	56,5	87	26	15	30	1,82	C-E-D
5030101006001600	600X1600	14	61	555	56,5	87	26	15	30	1,93	C-E-D
5030101006001800	600X1800	16	61	555	56,5	87	26	15	30	2,04	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101004001200	419	1429	545	1859
5030101004001400	442	1508	575	1961
5030101004001600	470	1603	611	2084
5030101004001800	501	1709	652	2224
5030101005001200	536	1828	697	2377
5030101005001400	560	1910	728	2483
5030101005001600	587	2002	764	2606
5030101005001800	618	2108	804	2742
5030101006001200	655	2234	852	2906
5030101006001400	678	2312	882	3008
5030101006001600	705	2405	917	3127
5030101006001800	736	2510	957	3264

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.91	9.92	0,06	432X1330X103
8.51	10.74	0,07	432X1530X103
9.10	11.58	0,08	432X1730X103
9.70	12.40	0,09	432X1930X103
9.65	11.93	0,08	532X1330X103
10.24	12.79	0,09	532X1530X103
10.84	13.66	0,10	532X1730X103
11.44	14.52	0,11	532X1930X103
11.33	13.89	0,09	632X1330X103
11.92	14.78	0,10	632X1530X103
12.52	15.69	0,12	632X1730X103
13.12	16.59	0,13	632X1930X103

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel