

GROSSE LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101404001200	400X1200	11	80	355	56,5	96,5	16,5	15	30	1,49	C-E-D
5030101404001400	400X1400	13	80	355	56,5	96,5	16,5	15	30	1,60	C-E-D
5030101404001600	400X1600	15	80	355	56,5	96,5	16,5	15	30	1,71	C-E-D
5030101404001800	400X1800	17	80	355	56,5	96,5	16,5	15	30	1,83	C-E-D
5030101405001200	500X1200	13	80	455	56,5	96,5	16,5	15	30	1,76	C-E-D
5030101405001400	500X1400	15	80	455	56,5	96,5	16,5	15	30	1,88	C-E-D
5030101405001600	500X1600	17	80	455	56,5	96,5	16,5	15	30	1,99	C-E-D
5030101405001800	500X1800	19	80	455	56,5	96,5	16,5	15	30	2,10	C-E-D
5030101406001200	600X1200	15	80	555	56,5	96,5	16,5	15	30	2,04	C-E-D
5030101406001400	600X1400	17	80	555	56,5	96,5	16,5	15	30	2,16	C-E-D
5030101406001600	600X1600	19	80	555	56,5	96,5	16,5	15	30	2,27	C-E-D
5030101406001800	600X1800	21	80	555	56,5	96,5	16,5	15	30	2,38	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101404001200	524	1787	682	2326
5030101404001400	548	1869	713	2432
5030101404001600	575	1961	748	2551
5030101404001800	606	2067	788	2688
5030101405001200	667	2275	868	2960
5030101405001400	690	2353	897	3059
5030101405001600	717	2445	933	3182
5030101405001800	749	2555	974	3322
5030101406001200	811	2766	1055	3598
5030101406001400	834	2844	1085	3700
5030101406001600	861	2937	1120	3820
5030101406001800	892	3042	1160	3956

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.58	11.64	0,08	432X1330X122
10.17	12.48	0,09	432X1530X122
10.77	13.30	0,10	432X1730X122
11.37	14.14	0,11	432X1930X122
11.78	14.12	0,09	532X1330X122
12.38	14.99	0,10	532X1530X122
12.98	15.86	0,12	532X1730X122
13.58	16.73	0,13	532X1930X122
13.93	16.54	0,11	632X1330X122
14.53	17.45	0,12	632X1530X122
15.13	18.35	0,14	632X1730X122
15.72	19.27	0,15	632X1930X122

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel