

LETTON LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101504001200	400X1200	9	60	355	56,5	86,5	26,5	15	30	1,35	C-E-D
5030101504001400	400X1400	11	60	355	56,5	86,5	26,5	15	30	1,46	C-E-D
5030101504001600	400X1600	13	60	355	56,5	86,5	26,5	15	30	1,58	C-E-D
5030101504001800	400X1800	15	60	355	56,5	86,5	26,5	15	30	1,69	C-E-D
5030101505001200	500X1200	10	60	455	56,5	86,5	26,5	15	30	1,56	C-E-D
5030101505001400	500X1400	12	60	455	56,5	86,5	26,5	15	30	1,67	C-E-D
5030101505001600	500X1600	14	60	455	56,5	86,5	26,5	15	30	1,79	C-E-D
5030101505001800	500X1800	16	60	455	56,5	86,5	26,5	15	30	1,90	C-E-D
5030101506001200	600X1200	11	60	555	56,5	86,5	26,5	15	30	1,77	C-E-D
5030101506001400	600X1400	13	60	555	56,5	86,5	26,5	15	30	1,88	C-E-D
5030101506001600	600X1600	15	60	555	56,5	86,5	26,5	15	30	2,00	C-E-D
5030101506001800	600X1800	17	60	555	56,5	86,5	26,5	15	30	2,11	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101504001200	449	1532	584	1992
5030101504001400	472	1610	614	2094
5030101504001600	500	1705	650	2217
5030101504001800	531	1811	691	2357
5030101505001200	559	1907	727	2480
5030101505001400	582	1985	757	2582
5030101505001600	610	2081	793	2705
5030101505001800	641	2186	834	2844
5030101506001200	670	2285	871	2971
5030101506001400	694	2367	903	3080
5030101506001600	721	2459	938	3199
5030101506001800	752	2565	978	3335

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.23	10.24	0,06	432X1330X102
8.83	11.07	0,07	432X1530X102
9.43	11.89	0,08	432X1730X102
10.03	12.72	0,09	432X1930X102
9.73	12.01	0,08	532X1330X102
10.33	12.87	0,09	532X1530X102
10.92	13.75	0,10	532X1730X102
11.52	14.61	0,11	532X1930X102
11.16	13.73	0,09	632X1330X102
11.76	14.62	0,10	632X1530X102
12.36	15.53	0,12	632X1730X102
12.95	16.42	0,13	632X1930X102

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel