

MOCCA LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101604001200	400X1200	8	39	355	56,5	96,5	43	15	30	1,28	C-E-D
5030101604001400	400X1400	10	39	355	56,5	96,5	43	15	30	1,40	C-E-D
5030101604001600	400X1600	12	39	355	56,5	96,5	43	15	30	1,51	C-E-D
5030101604001800	400X1800	14	39	355	56,5	96,5	43	15	30	1,62	C-E-D
5030101605001200	500X1200	9	39	455	56,5	96,5	43	15	30	1,49	C-E-D
5030101605001400	500X1400	11	39	455	56,5	96,5	43	15	30	1,61	C-E-D
5030101605001600	500X1600	13	39	455	56,5	96,5	43	15	30	1,72	C-E-D
5030101605001800	500X1800	15	39	455	56,5	96,5	43	15	30	1,83	C-E-D
5030101606001200	600X1200	10	39	555	56,5	96,5	43	15	30	1,70	C-E-D
5030101606001400	600X1400	12	39	555	56,5	96,5	43	15	30	1,82	C-E-D
5030101606001600	600X1600	14	39	555	56,5	96,5	43	15	30	1,93	C-E-D
5030101606001800	600X1800	16	39	555	56,5	96,5	43	15	30	2,04	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101604001200	384	1310	500	1705
5030101604001400	408	1392	531	1811
5030101604001600	435	1484	566	1931
5030101604001800	466	1590	606	2067
5030101605001200	484	1651	630	2149
5030101605001400	507	1729	660	2251
5030101605001600	534	1821	695	2370
5030101605001800	565	1927	735	2507
5030101606001200	585	1995	761	2596
5030101606001400	608	2074	791	2698
5030101606001600	635	2166	826	2817
5030101606001800	667	2275	868	2960

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7,28	9,19	0,05	432X1330X81
7,88	10,02	0,06	432X1530X81
8,48	10,84	0,07	432X1730X81
9,08	11,65	0,07	432X1930X81
8,71	10,88	0,06	532X1330X81
9,31	11,74	0,07	532X1530X81
9,90	12,60	0,08	532X1730X81
10,50	13,45	0,09	532X1930X81
10,08	12,51	0,07	632X1330X81
10,67	13,40	0,08	632X1530X81
11,27	14,30	0,09	632X1730X81
11,87	15,19	0,10	632X1930X81

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel