

NETIA LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101704001200	400X1200	10	55	355	56,5	94,5	43	15	30	1,42	C-E-D
5030101704001400	400X1400	12	55	355	56,5	94,5	43	15	30	1,53	C-E-D
5030101704001600	400X1600	14	55	355	56,5	94,5	43	15	30	1,65	C-E-D
5030101704001800	400X1800	16	55	355	56,5	94,5	43	15	30	1,76	C-E-D
5030101705001200	500X1200	12	55	455	56,5	94,5	43	15	30	1,70	C-E-D
5030101705001400	500X1400	14	55	455	56,5	94,5	43	15	30	1,81	C-E-D
5030101705001600	500X1600	16	55	455	56,5	94,5	43	15	30	1,92	C-E-D
5030101705001800	500X1800	18	55	455	56,5	94,5	43	15	30	2,04	C-E-D
5030101706001200	600X1200	14	55	555	56,5	94,5	43	15	30	1,98	C-E-D
5030101706001400	600X1400	16	55	555	56,5	94,5	43	15	30	2,09	C-E-D
5030101706001600	600X1600	18	55	555	56,5	94,5	43	15	30	2,20	C-E-D
5030101706001800	600X1800	20	55	555	56,5	94,5	43	15	30	2,31	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101704001200	451	1538	587	2002
5030101704001400	475	1620	618	2108
5030101704001600	502	1712	653	2227
5030101704001800	533	1818	693	2364
5030101705001200	585	1995	761	2596
5030101705001400	609	2077	792	2701
5030101705001600	636	2169	827	2821
5030101705001800	667	2275	868	2960
5030101706001200	720	2456	936	3192
5030101706001400	743	2534	966	3295
5030101706001600	770	2626	1001	3414
5030101706001800	802	2735	1043	3557

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.53	9.48	0,06	432X1330X97
8.12	10.31	0,07	432X1530X97
8.72	11.13	0,08	432X1730X97
9.32	11.95	0,09	432X1930X97
9.07	11.30	0,07	532X1330X97
9.67	12.16	0,08	532X1530X97
10.27	13.01	0,09	532X1730X97
10.86	13.88	0,10	532X1930X97
10.56	13.04	0,09	632X1330X97
11.16	13.93	0,10	632X1530X97
11.75	14.83	0,11	632X1730X97
12.35	15.73	0,12	632X1930X97

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel