

NETIA DOUBLE LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101804001200	400X1200	10	77	355	56,5	95	18	15	30	1,42	C-E-D
5030101804001400	400X1400	12	77	355	56,5	95	18	15	30	1,53	C-E-D
5030101804001600	400X1600	14	77	355	56,5	95	18	15	30	1,65	C-E-D
5030101804001800	400X1800	16	77	355	56,5	95	18	15	30	1,76	C-E-D
5030101805001200	500X1200	12	77	455	56,5	95	18	15	30	1,70	C-E-D
5030101805001400	500X1400	14	77	455	56,5	95	18	15	30	1,81	C-E-D
5030101805001600	500X1600	16	77	455	56,5	95	18	15	30	1,92	C-E-D
5030101805001800	500X1800	18	77	455	56,5	95	18	15	30	2,04	C-E-D
5030101806001200	600X1200	14	77	555	56,5	95	18	15	30	1,98	C-E-D
5030101806001400	600X1400	16	77	555	56,5	95	18	15	30	2,09	C-E-D
5030101806001600	600X1600	18	77	555	56,5	95	18	15	30	2,20	C-E-D
5030101806001800	600X1800	20	77	555	56,5	95	18	15	30	2,31	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101804001200	516	1760	671	2289
5030101804001400	540	1842	702	2394
5030101804001600	567	1934	738	2517
5030101804001800	598	2040	778	2653
5030101805001200	682	2326	887	3025
5030101805001400	705	2405	917	3127
5030101805001600	732	2497	952	3247
5030101805001800	764	2606	994	3390
5030101806001200	849	2896	1104	3765
5030101806001400	873	2977	1135	3871
5030101806001600	900	3069	1170	3990
5030101806001800	931	3175	1211	4130

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.47	10.52	0,07	432X1330X119
9.06	11.34	0,08	432X1530X119
9.66	12.18	0,09	432X1730X119
10.26	13.02	0,10	432X1930X119
10.48	12.81	0,09	532X1330X119
11.08	13.68	0,10	532X1530X119
11.68	14.54	0,11	532X1730X119
12.27	15.41	0,13	532X1930X119
12.44	15.04	0,11	632X1330X119
13.04	15.95	0,12	632X1530X119
13.63	16.85	0,14	632X1730X119
14.23	17.76	0,15	632X1930X119

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel