

ORIENT LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030101904001200	400X1200	9	60	355	56,5	86,5	26,5	15	30	1,35	C-E-D
5030101904001400	400X1400	11	60	355	56,5	86,5	26,5	15	30	1,46	C-E-D
5030101904001600	400X1600	13	60	355	56,5	86,5	26,5	15	30	1,58	C-E-D
5030101904001800	400X1800	15	60	355	56,5	86,5	26,5	15	30	1,69	C-E-D
5030101905001200	500X1200	10	60	455	56,5	86,5	26,5	15	30	1,56	C-E-D
5030101905001400	500X1400	12	60	455	56,5	86,5	26,5	15	30	1,68	C-E-D
5030101905001600	500X1600	14	60	455	56,5	86,5	26,5	15	30	1,79	C-E-D
5030101905001800	500X1800	16	60	455	56,5	86,5	26,5	15	30	1,90	C-E-D
5030101906001200	600X1200	12	60	555	56,5	86,5	26,5	15	30	1,84	C-E-D
5030101906001400	600X1400	14	60	555	56,5	86,5	26,5	15	30	1,95	C-E-D
5030101906001600	600X1600	16	60	555	56,5	86,5	26,5	15	30	2,07	C-E-D
5030101906001800	600X1800	18	60	555	56,5	86,5	26,5	15	30	2,18	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030101904001200	482	1644	627	2139
5030101904001400	506	1726	658	2244
5030101904001600	533	1818	693	2364
5030101904001800	564	1924	734	2503
5030101905001200	592	2019	770	2626
5030101905001400	616	2101	801	2732
5030101905001600	643	2193	836	2851
5030101905001800	674	2299	877	2991
5030101906001200	781	2664	1016	3465
5030101906001400	804	2742	1046	3567
5030101906001600	831	2834	1081	3687
5030101906001800	863	2943	1122	3827

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.20	10.21	0,06	432X1330X102
8.80	11.04	0,07	432X1530X102
9.40	11.86	0,08	432X1730X102
10.	12.69	0,09	432X1930X102
9.71	11.99	0,08	532X1330X102
10.31	12.85	0,09	532X1530X102
10.90	13.73	0,10	532X1730X102
11.50	14.59	0,11	532X1930X102
11.92	14.48	0,09	632X1330X102
12.52	15.38	0,10	632X1530X102
13.11	16.28	0,12	632X1730X102
13.71	17.18	0,13	632X1930X102

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel