

URLA LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030102204001200	400X1200	10	55	355	56,5	93,5	43	15	30	1,42	C-E-D
5030102204001400	400X1400	12	55	355	56,5	93,5	43	15	30	1,53	C-E-D
5030102204001600	400X1600	14	55	355	56,5	93,5	43	15	30	1,65	C-E-D
5030102204001800	400X1800	16	55	355	56,5	93,5	43	15	30	1,76	C-E-D
5030102205001200	500X1200	12	55	455	56,5	93,5	43	15	30	1,70	C-E-D
5030102205001400	500X1400	14	55	455	56,5	93,5	43	15	30	1,81	C-E-D
5030102205001600	500X1600	16	55	455	56,5	93,5	43	15	30	1,92	C-E-D
5030102205001800	500X1800	18	55	455	56,5	93,5	43	15	30	2,04	C-E-D
5030102206001200	600X1200	14	55	555	56,5	93,5	43	15	30	1,98	C-E-D
5030102206001400	600X1400	16	55	555	56,5	93,5	43	15	30	2,09	C-E-D
5030102206001600	600X1600	18	55	555	56,5	93,5	43	15	30	2,20	C-E-D
5030102206001800	600X1800	20	55	555	56,5	93,5	43	15	30	2,31	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030102204001200	417	1422	543	1852
5030102204001400	441	1504	574	1958
5030102204001600	468	1596	609	2077
5030102204001800	499	1702	649	2214
5030102205001200	533	1818	693	2364
5030102205001400	557	1900	725	2473
5030102205001600	584	1992	760	2592
5030102205001800	615	2098	800	2728
5030102206001200	651	2220	847	2889
5030102206001400	675	2302	878	2994
5030102206001600	702	2394	913	3114
5030102206001800	733	2500	953	3250

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.65	9.61	0,06	432X1330X97
8.25	10.44	0,07	432X1530X97
8.85	11.26	0,08	432X1730X97
9.44	12.08	0,09	432X1930X97
9.26	11.49	0,07	532X1330X97
9.86	12.35	0,08	532X1530X97
10.46	13.20	0,09	532X1730X97
11.06	14.07	0,10	532X1930X97
10.82	13.30	0,09	632X1330X97
11.41	14.19	0,10	632X1530X97
12.01	15.09	0,11	632X1730X97
12.61	15.99	0,12	632X1930X97

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel