

URLA DOUBLE LINE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030102304001200	400X1200	10	75	355	56,5	94	19	15	30	1,42	C-E-D
5030102304001400	400X1400	12	75	355	56,5	94	19	15	30	1,53	C-E-D
5030102304001600	400X1600	14	75	355	56,5	94	19	15	30	1,65	C-E-D
5030102304001800	400X1800	16	75	355	56,5	94	19	15	30	1,76	C-E-D
5030102305001200	500X1200	12	75	455	56,5	94	19	15	30	1,70	C-E-D
5030102305001400	500X1400	14	75	455	56,5	94	19	15	30	1,81	C-E-D
5030102305001600	500X1600	16	75	455	56,5	94	19	15	30	1,92	C-E-D
5030102305001800	500X1800	18	75	455	56,5	94	19	15	30	2,04	C-E-D
5030102306001200	600X1200	14	75	555	56,5	94	19	15	30	1,98	C-E-D
5030102306001400	600X1400	16	75	555	56,5	94	19	15	30	2,09	C-E-D
5030102306001600	600X1600	18	75	555	56,5	94	19	15	30	2,20	C-E-D
5030102306001800	600X1800	20	75	555	56,5	94	19	15	30	2,31	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030102304001200	465	1586	605	2064
5030102304001400	489	1668	636	2169
5030102304001600	516	1760	671	2289
5030102304001800	547	1866	712	2428
5030102305001200	606	2067	788	2688
5030102305001400	629	2145	818	2790
5030102305001600	656	2237	853	2909
5030102305001800	687	2343	894	3049
5030102306001200	747	2548	972	3315
5030102306001400	771	2630	1003	3421
5030102306001600	798	2722	1038	3540
5030102306001800	829	2827	1078	3676

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.48	10.52	0,07	432X1330X117
9.08	11.36	0,08	432X1530X117
9.68	12.20	0,09	432X1730X117
10.27	13.02	0,10	432X1930X117
10.51	12.82	0,09	532X1330X117
11.10	13.69	0,10	532X1530X117
11.70	14.56	0,11	532X1730X117
12.30	15.44	0,13	532X1930X117
12.47	15.07	0,10	632X1330X117
13.07	15.98	0,12	632X1530X117
13.67	16.87	0,13	632X1730X117
14.26	17.78	0,15	632X1930X117

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel