

VOGUE LINE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

| MODEL CODE       | Width x Height<br>( W x H ) | Tube   | Depth<br>(D) | Pipe<br>Centers<br>(A) | Wall to Pipe<br>Centers<br>(L) | Depth From<br>Wall<br>(K) | Wall To<br>Radiator Back<br>(M) | Space Between<br>Tubes<br>(E) | Tube Width<br>(F) | Water<br>Volume | Fuel<br>Type |
|------------------|-----------------------------|--------|--------------|------------------------|--------------------------------|---------------------------|---------------------------------|-------------------------------|-------------------|-----------------|--------------|
|                  | mm                          | pieces | mm           | mm                     | mm                             | mm                        | mm                              | mm                            | mm                | L               |              |
| 5030102505001200 | 500X1200                    | 8      | 45           | 455                    | 56,5                           | 84,5                      | 43                              | 15                            | 30                | 1,43            | C-E-D        |
| 5030102505001400 | 500X1400                    | 10     | 45           | 455                    | 56,5                           | 84,5                      | 43                              | 15                            | 30                | 1,54            | C-E-D        |
| 5030102505001600 | 500X1600                    | 12     | 45           | 455                    | 56,5                           | 84,5                      | 43                              | 15                            | 30                | 1,65            | C-E-D        |
| 5030102505001800 | 500X1800                    | 14     | 45           | 455                    | 56,5                           | 84,5                      | 43                              | 15                            | 30                | 1,76            | C-E-D        |

HEAT OUTPUTS INFORMATION

| MODEL CODE       | Heat Outputs<br>ΔT 50 °C |      | Heat Outputs<br>ΔT 60 °C |      |
|------------------|--------------------------|------|--------------------------|------|
|                  | Watt                     | Btu  | Watt                     | Btu  |
| 5030102505001200 | 462                      | 1576 | 601                      | 2050 |
| 5030102505001400 | 485                      | 1654 | 631                      | 2152 |
| 5030102505001600 | 512                      | 1746 | 666                      | 2272 |
| 5030102505001800 | 543                      | 1852 | 706                      | 2408 |

LOGISTICS INFORMATION

| Net<br>Weight | Gross<br>Weight | Package<br>Volume | Package<br>Dimensions<br>( W x H x D ) |
|---------------|-----------------|-------------------|----------------------------------------|
| kg            | kg              | m³                | mm                                     |
| 9.33          | 11.52           | 0,07              | 532X1330X87                            |
| 9.93          | 12.37           | 0,08              | 532X1530X87                            |
| 10.52         | 13.23           | 0,09              | 532X1730X87                            |
| 11.12         | 14.10           | 0,09              | 532X1930X87                            |

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel