

ALPHA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030102704001200	400X1200	10	47	355	56,5	93,5	43	15	30	1,38	C-E-D
5030102704001400	400X1400	14	47	355	56,5	93,5	43	15	30	1,49	C-E-D
5030102704001600	400X1600	18	47	355	56,5	93,5	43	15	30	1,60	C-E-D
5030102704001800	400X1800	22	47	355	56,5	93,5	43	15	30	1,72	C-E-D
5030102705001200	500X1200	12	47	455	56,5	93,5	43	15	30	1,68	C-E-D
5030102705001400	500X1400	16	47	455	56,5	93,5	43	15	30	1,80	C-E-D
5030102705001600	500X1600	20	47	455	56,5	93,5	43	15	30	1,91	C-E-D
5030102705001800	500X1800	24	47	455	56,5	93,5	43	15	30	2,02	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030102704001200	398	1358	518	1767
5030102704001400	422	1440	549	1873
5030102704001600	449	1532	584	1992
5030102704001800	480	1637	624	2128
5030102705001200	560	1910	728	2483
5030102705001400	583	1989	758	2585
5030102705001600	610	2081	793	2705
5030102705001800	642	2190	835	2848

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7,65	9,58	0,06	432X1330X89
8,31	10,47	0,06	432X1530X89
8,96	11,35	0,07	432X1730X89
9,62	12,23	0,08	432X1930X89
9,76	11,95	0,07	532X1330X89
10,41	12,87	0,08	532X1530X89
11,07	13,79	0,09	532X1730X89
11,72	14,71	0,10	532X1930X89

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel