

ART PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030102804001200	400X1200	11	44	355	56,5	82,5	43	15	30	1,44	C-E-D
5030102804001400	400X1400	15	44	355	56,5	82,5	43	15	30	1,56	C-E-D
5030102804001600	400X1600	19	44	355	56,5	82,5	43	15	30	1,67	C-E-D
5030102804001800	400X1800	23	44	355	56,5	82,5	43	15	30	1,78	C-E-D
5030102805001200	500X1200	13	44	455	56,5	82,5	43	15	30	1,75	C-E-D
5030102805001400	500X1400	17	44	455	56,5	82,5	43	15	30	1,86	C-E-D
5030102805001600	500X1600	21	44	455	56,5	82,5	43	15	30	1,98	C-E-D
5030102805001800	500X1800	25	44	455	56,5	82,5	43	15	30	2,09	C-E-D
5030102806001200	600X1200	14	44	555	56,5	82,5	43	15	30	1,99	C-E-D
5030102806001400	600X1400	18	44	555	56,5	82,5	43	15	30	2,10	C-E-D
5030102806001600	600X1600	22	44	555	56,5	82,5	43	15	30	2,22	C-E-D
5030102806001800	600X1800	26	44	555	56,5	82,5	43	15	30	2,33	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030102804001200	407	1388	530	1808
5030102804001400	430	1467	559	1907
5030102804001600	457	1559	595	2029
5030102804001800	489	1668	636	2169
5030102805001200	535	1825	696	2374
5030102805001400	558	1903	726	2476
5030102805001600	586	1999	762	2599
5030102805001800	617	2104	803	2739
5030102806001200	622	2122	809	2759
5030102806001400	646	2203	840	2865
5030102806001600	673	2295	875	2984
5030102806001800	704	2401	916	3124

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.84	9.76	0,05	432X1330X86
8.50	10.64	0,06	432X1530X86
9.15	11.53	0,07	432X1730X86
9.80	12.41	0,08	432X1930X86
9.67	11.85	0,07	532X1330X86
10.32	12.77	0,08	532X1530X86
10.98	13.69	0,08	532X1730X86
11.63	14.60	0,09	532X1930X86
10.96	13.41	0,08	632X1330X86
11.61	14.36	0,09	632X1530X86
12.26	15.31	0,10	632X1730X86
12.92	16.25	0,11	632X1930X86

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel