

ART DOUBLE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030102904001200	400X1200	11	52	355	56,5	82,5	30,5	15	30	1,44	C-E-D
5030102904001400	400X1400	15	52	355	56,5	82,5	30,5	15	30	1,56	C-E-D
5030102904001600	400X1600	19	52	355	56,5	82,5	30,5	15	30	1,67	C-E-D
5030102904001800	400X1800	23	52	355	56,5	82,5	30,5	15	30	1,78	C-E-D
5030102905001200	500X1200	13	52	455	56,5	82,5	30,5	15	30	1,75	C-E-D
5030102905001400	500X1400	17	52	455	56,5	82,5	30,5	15	30	1,86	C-E-D
5030102905001600	500X1600	21	52	455	56,5	82,5	30,5	15	30	1,98	C-E-D
5030102905001800	500X1800	25	52	455	56,5	82,5	30,5	15	30	2,09	C-E-D
5030102906001200	600X1200	14	52	555	56,5	82,5	30,5	15	30	1,99	C-E-D
5030102906001400	600X1400	18	52	555	56,5	82,5	30,5	15	30	2,10	C-E-D
5030102906001600	600X1600	22	52	555	56,5	82,5	30,5	15	30	2,22	C-E-D
5030102906001800	600X1800	26	52	555	56,5	82,5	30,5	15	30	2,33	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030102904001200	438	1494	570	1944
5030102904001400	462	1576	601	2050
5030102904001600	489	1668	636	2169
5030102904001800	520	1774	676	2306
5030102905001200	588	2006	765	2609
5030102905001400	611	2084	795	2711
5030102905001600	639	2179	831	2834
5030102905001800	670	2285	871	2971
5030102906001200	686	2340	892	3042
5030102906001400	710	2422	923	3148
5030102906001600	737	2514	959	3271
5030102906001800	768	2619	999	3407

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.58	10.53	0,06	432X1330X94
9.23	11.40	0,07	432X1530X94
9.89	12.30	0,08	432X1730X94
10.54	13.17	0,08	432X1930X94
10.90	13.11	0,07	532X1330X94
11.55	14.02	0,08	532X1530X94
12.21	14.95	0,09	532X1730X94
12.86	15.86	0,10	532X1930X94
12.43	14.90	0,08	632X1330X94
13.09	15.86	0,10	632X1530X94
13.74	16.82	0,11	632X1730X94
14.39	17.77	0,12	632X1930X94

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel