

ASITA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030103004001200	400X1200	11	47	355	56,5	86,5	43	15	30	1,44	C-E-D
5030103004001400	400X1400	15	47	355	56,5	86,5	43	15	30	1,56	C-E-D
5030103004001600	400X1600	19	47	355	56,5	86,5	43	15	30	1,67	C-E-D
5030103004001800	400X1800	23	47	355	56,5	86,5	43	15	30	1,78	C-E-D
5030103005001200	500X1200	12	47	455	56,5	86,5	43	15	30	1,68	C-E-D
5030103005001400	500X1400	16	47	455	56,5	86,5	43	15	30	1,80	C-E-D
5030103005001600	500X1600	20	47	455	56,5	86,5	43	15	30	1,91	C-E-D
5030103005001800	500X1800	24	47	455	56,5	86,5	43	15	30	2,02	C-E-D
5030103006001200	600X1200	13	47	555	56,5	86,5	43	15	30	1,92	C-E-D
5030103006001400	600X1400	17	47	555	56,5	86,5	43	15	30	2,03	C-E-D
5030103006001600	600X1600	21	47	555	56,5	86,5	43	15	30	2,15	C-E-D
5030103006001800	600X1800	25	47	555	56,5	86,5	43	15	30	2,26	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030103004001200	462	1576	601	2050
5030103004001400	486	1658	632	2156
5030103004001600	513	1750	667	2275
5030103004001800	544	1856	708	2415
5030103005001200	570	1944	741	2527
5030103005001400	593	2023	771	2630
5030103005001600	621	2118	808	2756
5030103005001800	652	2224	848	2892
5030103006001200	679	2316	883	3012
5030103006001400	703	2398	914	3117
5030103006001600	730	2490	949	3237
5030103006001800	761	2596	990	3376

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.24	10.17	0,06	432X1330X89
8.90	11.06	0,06	432X1530X89
9.55	11.94	0,07	432X1730X89
10.20	12.81	0,08	432X1930X89
9.73	11.93	0,07	532X1330X89
10.38	12.84	0,08	532X1530X89
11.04	13.76	0,09	532X1730X89
11.69	14.68	0,10	532X1930X89
11.14	13.60	0,08	632X1330X89
11.79	14.55	0,09	632X1530X89
12.45	15.50	0,10	632X1730X89
13.10	16.45	0,11	632X1930X89

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel