

ASITA DOUBLE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030103104001200	400X1200	11	61	355	56,5	87	26	15	30	1,44	C-E-D
5030103104001400	400X1400	15	61	355	56,5	87	26	15	30	1,56	C-E-D
5030103104001600	400X1600	19	61	355	56,5	87	26	15	30	1,67	C-E-D
5030103104001800	400X1800	23	61	355	56,5	87	26	15	30	1,78	C-E-D
5030103105001200	500X1200	12	61	455	56,5	87	26	15	30	1,68	C-E-D
5030103105001400	500X1400	16	61	455	56,5	87	26	15	30	1,80	C-E-D
5030103105001600	500X1600	20	61	455	56,5	87	26	15	30	1,91	C-E-D
5030103105001800	500X1800	24	61	455	56,5	87	26	15	30	2,02	C-E-D
5030103106001200	600X1200	13	61	555	56,5	87	26	15	30	1,92	C-E-D
5030103106001400	600X1400	17	61	555	56,5	87	26	15	30	2,03	C-E-D
5030103106001600	600X1600	21	61	555	56,5	87	26	15	30	2,15	C-E-D
5030103106001800	600X1800	25	61	555	56,5	87	26	15	30	2,26	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030103104001200	531	1811	691	2357
5030103104001400	554	1890	721	2459
5030103104001600	581	1982	756	2578
5030103104001800	613	2091	797	2718
5030103105001200	659	2248	857	2923
5030103105001400	682	2326	887	3025
5030103105001600	709	2418	922	3145
5030103105001800	741	2527	964	3288
5030103106001200	788	2688	1025	3496
5030103106001400	812	2769	1056	3601
5030103106001600	839	2861	1091	3721
5030103106001800	870	2967	1131	3857

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.38	11.40	0,06	432X1330X103
10.04	12.27	0,07	432X1530X103
10.69	13.17	0,08	432X1730X103
11.34	14.04	0,09	432X1930X103
11.28	13.56	0,08	532X1330X103
11.93	14.48	0,09	532X1530X103
12.59	15.41	0,10	532X1730X103
13.24	16.33	0,11	532X1930X103
13.10	15.66	0,09	632X1330X103
13.75	16.61	0,10	632X1530X103
14.41	17.57	0,12	632X1730X103
15.06	18.54	0,13	632X1930X103

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel