

AVVO PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030103204001200	400X1200	13	97	355	56,5	105	8	15	30	1,55	C-E-D
5030103204001400	400X1400	17	97	355	56,5	105	8	15	30	1,66	C-E-D
5030103204001600	400X1600	21	97	355	56,5	105	8	15	30	1,78	C-E-D
5030103204001800	400X1800	25	97	355	56,5	105	8	15	30	1,89	C-E-D
5030103205001200	500X1200	14	97	455	56,5	105	8	15	30	1,78	C-E-D
5030103205001400	500X1400	18	97	455	56,5	105	8	15	30	1,90	C-E-D
5030103205001600	500X1600	22	97	455	56,5	105	8	15	30	2,01	C-E-D
5030103205001800	500X1800	26	97	455	56,5	105	8	15	30	2,12	C-E-D
5030103206001200	600X1200	16	97	555	56,5	105	8	15	30	2,08	C-E-D
5030103206001400	600X1400	20	97	555	56,5	105	8	15	30	2,19	C-E-D
5030103206001600	600X1600	24	97	555	56,5	105	8	15	30	2,31	C-E-D
5030103206001800	600X1800	28	97	555	56,5	105	8	15	30	2,42	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030103204001200	541	1845	704	2401
5030103204001400	565	1927	735	2507
5030103204001600	592	2019	770	2626
5030103204001800	623	2125	810	2763
5030103205001200	637	2173	829	2827
5030103205001400	660	2251	858	2926
5030103205001600	688	2347	895	3052
5030103205001800	719	2452	935	3189
5030103206001200	787	2684	1024	3492
5030103206001400	810	2763	1053	3591
5030103206001600	837	2855	1089	3714
5030103206001800	869	2964	1130	3854

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.71	11.83	0,08	432X1330X139
10.37	12.72	0,10	432X1530X139
11.02	13.61	0,11	432X1730X139
11.68	14.51	0,12	432X1930X139
11.27	13.66	0,10	532X1330X139
11.92	14.59	0,12	532X1530X139
12.58	15.52	0,13	532X1730X139
13.23	16.45	0,15	532X1930X139
13.40	16.06	0,12	632X1330X139
14.05	17.03	0,14	632X1530X139
14.70	17.99	0,16	632X1730X139
15.36	18.96	0,17	632X1930X139

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel