

GIA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030103804001200	400X1200	10	47	355	56,5	90,5	43	15	30	1,38	C-E-D
5030103804001400	400X1400	14	47	355	56,5	90,5	43	15	30	1,49	C-E-D
5030103804001600	400X1600	18	47	355	56,5	90,5	43	15	30	1,60	C-E-D
5030103804001800	400X1800	22	47	355	56,5	90,5	43	15	30	1,72	C-E-D
5030103805001200	500X1200	11	47	455	56,5	90,5	43	15	30	1,61	C-E-D
5030103805001400	500X1400	15	47	455	56,5	90,5	43	15	30	1,73	C-E-D
5030103805001600	500X1600	19	47	455	56,5	90,5	43	15	30	1,84	C-E-D
5030103805001800	500X1800	23	47	455	56,5	90,5	43	15	30	1,95	C-E-D
5030103806001200	600X1200	12	47	555	56,5	90,5	43	15	30	1,85	C-E-D
5030103806001400	600X1400	16	47	555	56,5	90,5	43	15	30	1,97	C-E-D
5030103806001600	600X1600	20	47	555	56,5	90,5	43	15	30	2,08	C-E-D
5030103806001800	600X1800	24	47	555	56,5	90,5	43	15	30	2,19	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030103804001200	412	1405	536	1828
5030103804001400	436	1487	567	1934
5030103804001600	463	1579	602	2053
5030103804001800	494	1685	643	2193
5030103805001200	522	1781	679	2316
5030103805001400	546	1862	710	2422
5030103805001600	573	1954	745	2541
5030103805001800	604	2060	786	2681
5030103806001200	634	2162	825	2814
5030103806001400	657	2241	855	2916
5030103806001600	685	2336	891	3039
5030103806001800	716	2442	931	3175

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.57	9.50	0,06	432X1330X89
8.22	10.38	0,06	432X1530X89
8.88	11.27	0,07	432X1730X89
9.53	12.14	0,08	432X1930X89
9.03	11.22	0,07	532X1330X89
9.68	12.14	0,08	532X1530X89
10.34	13.06	0,09	532X1730X89
10.99	13.98	0,10	532X1930X89
10.41	12.87	0,08	632X1330X89
11.06	13.82	0,09	632X1530X89
11.72	14.77	0,10	632X1730X89
12.37	15.73	0,11	632X1930X89

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel