

GIA DOUBLE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030103904001200	400X1200	10	68	355	56,5	90,5	22,5	15	30	1,38	C-E-D
5030103904001400	400X1400	14	68	355	56,5	90,5	22,5	15	30	1,49	C-E-D
5030103904001600	400X1600	18	68	355	56,5	90,5	22,5	15	30	1,60	C-E-D
5030103904001800	400X1800	22	68	355	56,5	90,5	22,5	15	30	1,72	C-E-D
5030103905001200	500X1200	11	68	455	56,5	90,5	22,5	15	30	1,61	C-E-D
5030103905001400	500X1400	15	68	455	56,5	90,5	22,5	15	30	1,73	C-E-D
5030103905001600	500X1600	19	68	455	56,5	90,5	22,5	15	30	1,84	C-E-D
5030103905001800	500X1800	23	68	455	56,5	90,5	22,5	15	30	1,95	C-E-D
5030103906001200	600X1200	12	68	555	56,5	90,5	22,5	15	30	1,85	C-E-D
5030103906001400	600X1400	16	68	555	56,5	90,5	22,5	15	30	1,97	C-E-D
5030103906001600	600X1600	20	68	555	56,5	90,5	22,5	15	30	2,08	C-E-D
5030103906001800	600X1800	24	68	555	56,5	90,5	22,5	15	30	2,19	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030103904001200	454	1549	591	2016
5030103904001400	478	1630	622	2122
5030103904001600	505	1723	657	2241
5030103904001800	536	1828	697	2377
5030103905001200	585	1995	761	2596
5030103905001400	609	2077	792	2701
5030103905001600	636	2169	827	2821
5030103905001800	667	2275	868	2960
5030103906001200	718	2449	934	3185
5030103906001400	741	2527	964	3288
5030103906001600	768	2619	999	3407
5030103906001800	800	2728	1040	3547

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.33	10.37	0,07	432X1330X110
8.99	11.24	0,08	432X1530X110
9.64	12.14	0,09	432X1730X110
10.30	13.02	0,10	432X1930X110
10.18	12.48	0,08	532X1330X110
10.83	13.41	0,09	532X1530X110
11.48	14.34	0,11	532X1730X110
12.14	15.25	0,12	532X1930X110
11.94	14.52	0,10	632X1330X110
12.59	15.48	0,11	632X1530X110
13.25	16.44	0,13	632X1730X110
13.90	17.40	0,14	632X1930X110

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel