

GROSSE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104004001200	400X1200	13	80	355	56,5	96,5	16,5	15	30	1,58	C-E-D
5030104004001400	400X1400	17	80	355	56,5	96,5	16,5	15	30	1,69	C-E-D
5030104004001600	400X1600	21	80	355	56,5	96,5	16,5	15	30	1,81	C-E-D
5030104004001800	400X1800	25	80	355	56,5	96,5	16,5	15	30	1,92	C-E-D
5030104005001200	500X1200	15	80	455	56,5	96,5	16,5	15	30	1,89	C-E-D
5030104005001400	500X1400	19	80	455	56,5	96,5	16,5	15	30	2,00	C-E-D
5030104005001600	500X1600	23	80	455	56,5	96,5	16,5	15	30	2,11	C-E-D
5030104005001800	500X1800	27	80	455	56,5	96,5	16,5	15	30	2,23	C-E-D
5030104006001200	600X1200	17	80	555	56,5	96,5	16,5	15	30	2,19	C-E-D
5030104006001400	600X1400	21	80	555	56,5	96,5	16,5	15	30	2,31	C-E-D
5030104006001600	600X1600	25	80	555	56,5	96,5	16,5	15	30	2,42	C-E-D
5030104006001800	600X1800	29	80	555	56,5	96,5	16,5	15	30	2,53	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104004001200	554	1890	721	2459
5030104004001400	578	1971	752	2565
5030104004001600	605	2064	787	2684
5030104004001800	636	2169	827	2821
5030104005001200	707	2411	920	3138
5030104005001400	731	2493	951	3243
5030104005001600	758	2585	986	3363
5030104005001800	789	2691	1026	3499
5030104006001200	863	2943	1122	3827
5030104006001400	886	3022	1152	3929
5030104006001600	913	3114	1187	4048
5030104006001800	944	3220	1228	4188

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
10.11	12.18	0,08	432X1330X122
10.77	13.07	0,09	432X1530X122
11.42	13.95	0,10	432X1730X122
12.08	14.85	0,11	432X1930X122
12.50	14.83	0,09	532X1330X122
13.15	15.76	0,10	532X1530X122
13.81	16.69	0,12	532X1730X122
14.46	17.61	0,13	532X1930X122
14.77	17.38	0,11	632X1330X122
15.42	18.34	0,12	632X1530X122
16.08	19.30	0,14	632X1730X122
16.73	20.28	0,15	632X1930X122

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel