

LETTON PLUS		TECHNICAL INFORMATION										(For connection types, please refer to the last page)	
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type		
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L			
5030104104001200	400X1200	11	60	355	56,5	86,5	26,5	15	30	1,44	C-E-D		
5030104104001400	400X1400	15	60	355	56,5	86,5	26,5	15	30	1,56	C-E-D		
5030104104001600	400X1600	19	60	355	56,5	86,5	26,5	15	30	1,67	C-E-D		
5030104104001800	400X1800	23	60	355	56,5	86,5	26,5	15	30	1,78	C-E-D		
5030104105001200	500X1200	12	60	455	56,5	86,5	26,5	15	30	1,68	C-E-D		
5030104105001400	500X1400	16	60	455	56,5	86,5	26,5	15	30	1,80	C-E-D		
5030104105001600	500X1600	20	60	455	56,5	86,5	26,5	15	30	1,91	C-E-D		
5030104105001800	500X1800	24	60	455	56,5	86,5	26,5	15	30	2,02	C-E-D		
5030104106001200	600X1200	13	60	555	56,5	86,5	26,5	15	30	1,92	C-E-D		
5030104106001400	600X1400	17	60	555	56,5	86,5	26,5	15	30	2,03	C-E-D		
5030104106001600	600X1600	21	60	555	56,5	86,5	26,5	15	30	2,15	C-E-D		
5030104106001800	600X1800	25	60	555	56,5	86,5	26,5	15	30	2,26	C-E-D		

CONNECTIONS TYPE

SX

x

ZX

x

YP

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104104001200	479	1634	623	2125
5030104104001400	502	1712	653	2227
5030104104001600	529	1804	688	2347
5030104104001800	561	1914	730	2490
5030104105001200	600	2046	780	2660
5030104105001400	623	2125	810	2763
5030104105001600	650	2217	845	2882
5030104105001800	681	2323	886	3022
5030104106001200	722	2463	939	3202
5030104106001400	746	2544	970	3308
5030104106001600	773	2636	1005	3428
5030104106001800	804	2742	1046	3567

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.77	10.78	0,06	432X1330X102
9.43	11.66	0,07	432X1530X102
10.08	12.55	0,08	432X1730X102
10.73	13.43	0,09	432X1930X102
10.43	12.71	0,08	532X1330X102
11.08	13.63	0,09	532X1530X102
11.73	14.56	0,10	532X1730X102
12.39	15.47	0,11	532X1930X102
12.	14.56	0,09	632X1330X102
12.65	15.51	0,10	632X1530X102
13.31	16.48	0,12	632X1730X102
13.96	17.43	0,13	632X1930X102

C: Central Heating / E: Electric / D: Dual Fuel