

MOCCA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104204001200	400X1200	10	39	355	56,5	96,5	43	15	30	1,38	C-E-D
5030104204001400	400X1400	14	39	355	56,5	96,5	43	15	30	1,49	C-E-D
5030104204001600	400X1600	18	39	355	56,5	96,5	43	15	30	1,60	C-E-D
5030104204001800	400X1800	22	39	355	56,5	96,5	43	15	30	1,72	C-E-D
5030104205001200	500X1200	11	39	455	56,5	96,5	43	15	30	1,61	C-E-D
5030104205001400	500X1400	15	39	455	56,5	96,5	43	15	30	1,73	C-E-D
5030104205001600	500X1600	19	39	455	56,5	96,5	43	15	30	1,84	C-E-D
5030104205001800	500X1800	23	39	455	56,5	96,5	43	15	30	1,95	C-E-D
5030104206001200	600X1200	12	39	555	56,5	96,5	43	15	30	1,85	C-E-D
5030104206001400	600X1400	16	39	555	56,5	96,5	43	15	30	1,97	C-E-D
5030104206001600	600X1600	20	39	555	56,5	96,5	43	15	30	2,08	C-E-D
5030104206001800	600X1800	24	39	555	56,5	96,5	43	15	30	2,19	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104204001200	414	1412	539	1838
5030104204001400	437	1491	569	1941
5030104204001600	465	1586	605	2064
5030104204001800	496	1692	645	2200
5030104205001200	524	1787	682	2326
5030104205001400	548	1869	713	2432
5030104205001600	575	1961	748	2551
5030104205001800	606	2067	788	2688
5030104206001200	637	2173	829	2827
5030104206001400	660	2251	858	2926
5030104206001600	687	2343	894	3049
5030104206001800	719	2452	935	3189

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.82	9.73	0,05	432X1330X81
8.48	10.61	0,06	432X1530X81
9.13	11.49	0,07	432X1730X81
9.78	12.36	0,07	432X1930X81
9.41	11.58	0,06	532X1330X81
10.06	12.49	0,07	532X1530X81
10.72	13.41	0,08	532X1730X81
11.37	14.32	0,09	532X1930X81
10.91	13.34	0,07	632X1330X81
11.57	14.30	0,08	632X1530X81
12.22	15.25	0,09	632X1730X81
12.88	16.20	0,10	632X1930X81

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel