

NETIA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104304001200	400X1200	12	55	355	56,5	94,5	43	15	30	1,51	C-E-D
5030104304001400	400X1400	16	55	355	56,5	94,5	43	15	30	1,62	C-E-D
5030104304001600	400X1600	20	55	355	56,5	94,5	43	15	30	1,74	C-E-D
5030104304001800	400X1800	24	55	355	56,5	94,5	43	15	30	1,85	C-E-D
5030104305001200	500X1200	14	55	455	56,5	94,5	43	15	30	1,82	C-E-D
5030104305001400	500X1400	18	55	455	56,5	94,5	43	15	30	1,93	C-E-D
5030104305001600	500X1600	22	55	455	56,5	94,5	43	15	30	2,04	C-E-D
5030104305001800	500X1800	26	55	455	56,5	94,5	43	15	30	2,16	C-E-D
5030104306001200	600X1200	16	55	555	56,5	94,5	43	15	30	2,13	C-E-D
5030104306001400	600X1400	20	55	555	56,5	94,5	43	15	30	2,24	C-E-D
5030104306001600	600X1600	24	55	555	56,5	94,5	43	15	30	2,35	C-E-D
5030104306001800	600X1800	28	55	555	56,5	94,5	43	15	30	2,46	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104304001200	481	1641	626	2135
5030104304001400	505	1723	657	2241
5030104304001600	532	1815	692	2360
5030104304001800	563	1920	732	2497
5030104305001200	626	2135	814	2776
5030104305001400	649	2214	844	2879
5030104305001600	676	2306	879	2998
5030104305001800	707	2411	920	3138
5030104306001200	772	2633	1004	3424
5030104306001400	795	2711	1034	3526
5030104306001600	822	2804	1069	3646
5030104306001800	854	2913	1111	3789

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.06	10.02	0,06	432X1330X97
8.72	10.90	0,07	432X1530X97
9.37	11.78	0,08	432X1730X97
10.02	12.66	0,09	432X1930X97
9.77	11.99	0,07	532X1330X97
10.42	12.91	0,08	532X1530X97
11.08	13.82	0,09	532X1730X97
11.73	14.75	0,10	532X1930X97
11.40	13.88	0,09	632X1330X97
12.05	14.83	0,10	632X1530X97
12.70	15.78	0,11	632X1730X97
13.36	16.74	0,12	632X1930X97

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel