

NETIA DOUBLE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104404001200	400X1200	12	77	355	56,5	95	18	15	30	1,51	C-E-D
5030104404001400	400X1400	16	77	355	56,5	95	18	15	30	1,62	C-E-D
5030104404001600	400X1600	20	77	355	56,5	95	18	15	30	1,74	C-E-D
5030104404001800	400X1800	24	77	355	56,5	95	18	15	30	1,85	C-E-D
5030104405001200	500X1200	14	77	455	56,5	95	18	15	30	1,82	C-E-D
5030104405001400	500X1400	18	77	455	56,5	95	18	15	30	1,93	C-E-D
5030104405001600	500X1600	22	77	455	56,5	95	18	15	30	2,04	C-E-D
5030104405001800	500X1800	26	77	455	56,5	95	18	15	30	2,16	C-E-D
5030104406001200	600X1200	16	77	555	56,5	95	18	15	30	2,13	C-E-D
5030104406001400	600X1400	20	77	555	56,5	95	18	15	30	2,24	C-E-D
5030104406001600	600X1600	24	77	555	56,5	95	18	15	30	2,35	C-E-D
5030104406001800	600X1800	28	77	555	56,5	95	18	15	30	2,46	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104404001200	546	1862	710	2422
5030104404001400	570	1944	741	2527
5030104404001600	597	2036	777	2650
5030104404001800	628	2142	817	2786
5030104405001200	722	2463	939	3202
5030104405001400	746	2544	970	3308
5030104405001600	773	2636	1005	3428
5030104405001800	804	2742	1046	3567
5030104406001200	901	3073	1172	3997
5030104406001400	925	3155	1203	4103
5030104406001600	952	3247	1238	4222
5030104406001800	983	3353	1278	4358

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.	11.05	0,07	432X1330X119
9.66	11.94	0,08	432X1530X119
10.31	12.83	0,09	432X1730X119
10.96	13.72	0,10	432X1930X119
11.18	13.51	0,09	532X1330X119
11.83	14.43	0,10	532X1530X119
12.49	15.35	0,11	532X1730X119
13.14	16.28	0,13	532X1930X119
13.28	15.88	0,11	632X1330X119
13.93	16.84	0,12	632X1530X119
14.58	17.80	0,14	632X1730X119
15.24	18.76	0,15	632X1930X119

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel