

ORIENT PLUS		TECHNICAL INFORMATION										(For connection types, please refer to the last page)	
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type		
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L			
5030104504001200	400X1200	11	60	355	56,5	86,5	26,5	15	30	1,44	C-E-D		
5030104504001400	400X1400	15	60	355	56,5	86,5	26,5	15	30	1,56	C-E-D		
5030104504001600	400X1600	19	60	355	56,5	86,5	26,5	15	30	1,67	C-E-D		
5030104504001800	400X1800	23	60	355	56,5	86,5	26,5	15	30	1,78	C-E-D		
5030104505001200	500X1200	12	60	455	56,5	86,5	26,5	15	30	1,68	C-E-D		
5030104505001400	500X1400	16	60	455	56,5	86,5	26,5	15	30	1,80	C-E-D		
5030104505001600	500X1600	20	60	455	56,5	86,5	26,5	15	30	1,91	C-E-D		
5030104505001800	500X1800	24	60	455	56,5	86,5	26,5	15	30	2,02	C-E-D		
5030104506001200	600X1200	14	60	555	56,5	86,5	26,5	15	30	1,99	C-E-D		
5030104506001400	600X1400	18	60	555	56,5	86,5	26,5	15	30	2,10	C-E-D		
5030104506001600	600X1600	22	60	555	56,5	86,5	26,5	15	30	2,22	C-E-D		
5030104506001800	600X1800	26	60	555	56,5	86,5	26,5	15	30	2,33	C-E-D		

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104504001200	512	1746	666	2272
5030104504001400	535	1825	696	2374
5030104504001600	563	1920	732	2497
5030104504001800	594	2026	773	2636
5030104505001200	633	2159	823	2807
5030104505001400	656	2237	853	2909
5030104505001600	683	2330	888	3029
5030104505001800	714	2435	929	3168
5030104506001200	833	2841	1083	3694
5030104506001400	856	2919	1113	3796
5030104506001600	883	3012	1148	3915
5030104506001800	915	3121	1190	4058

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.74	10.75	0,06	432X1330X102
9.40	11.63	0,07	432X1530X102
10.05	12.52	0,08	432X1730X102
10.70	13.40	0,09	432X1930X102
10.41	12.69	0,08	532X1330X102
11.06	13.61	0,09	532X1530X102
11.71	14.54	0,10	532X1730X102
12.37	15.45	0,11	532X1930X102
12.76	15.32	0,09	632X1330X102
13.41	16.27	0,10	632X1530X102
14.06	17.23	0,12	632X1730X102
14.72	18.18	0,13	632X1930X102

CONNECTIONS TYPE

SX

x

ZX

x

YP

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel