

URLA PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104804001200	400X1200	12	55	355	56,5	93,5	43	15	30	1,51	C-E-D
5030104804001400	400X1400	16	55	355	56,5	93,5	43	15	30	1,62	C-E-D
5030104804001600	400X1600	20	55	355	56,5	93,5	43	15	30	1,74	C-E-D
5030104804001800	400X1800	24	55	355	56,5	93,5	43	15	30	1,85	C-E-D
5030104805001200	500X1200	14	55	455	56,5	93,5	43	15	30	1,82	C-E-D
5030104805001400	500X1400	18	55	455	56,5	93,5	43	15	30	1,93	C-E-D
5030104805001600	500X1600	22	55	455	56,5	93,5	43	15	30	2,04	C-E-D
5030104805001800	500X1800	26	55	455	56,5	93,5	43	15	30	2,16	C-E-D
5030104806001200	600X1200	16	55	555	56,5	93,5	43	15	30	2,13	C-E-D
5030104806001400	600X1400	20	55	555	56,5	93,5	43	15	30	2,24	C-E-D
5030104806001600	600X1600	24	55	555	56,5	93,5	43	15	30	2,35	C-E-D
5030104806001800	600X1800	28	55	555	56,5	93,5	43	15	30	2,46	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104804001200	447	1525	582	1985
5030104804001400	471	1607	613	2091
5030104804001600	498	1699	648	2210
5030104804001800	529	1804	688	2347
5030104805001200	574	1958	747	2548
5030104805001400	598	2040	778	2653
5030104805001600	625	2132	813	2773
5030104805001800	656	2237	853	2909
5030104806001200	703	2398	914	3117
5030104806001400	727	2480	946	3226
5030104806001600	754	2572	981	3346
5030104806001800	785	2677	1021	3482

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.19	10.15	0,06	432X1330X97
8.84	11.03	0,07	432X1530X97
9.50	11.91	0,08	432X1730X97
10.15	12.79	0,09	432X1930X97
9.96	12.19	0,07	532X1330X97
10.62	13.10	0,08	532X1530X97
11.27	14.01	0,09	532X1730X97
11.92	14.94	0,10	532X1930X97
11.65	14.13	0,09	632X1330X97
12.31	15.08	0,10	632X1530X97
12.96	16.04	0,11	632X1730X97
13.61	17.	0,12	632X1930X97

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel