

URLA DOUBLE PLUS

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030104904001200	400X1200	12	75	355	56,5	94	19	15	30	1,51	C-E-D
5030104904001400	400X1400	16	75	355	56,5	94	19	15	30	1,62	C-E-D
5030104904001600	400X1600	20	75	355	56,5	94	19	15	30	1,74	C-E-D
5030104904001800	400X1800	24	75	355	56,5	94	19	15	30	1,85	C-E-D
5030104905001200	500X1200	14	75	455	56,5	94	19	15	30	1,82	C-E-D
5030104905001400	500X1400	18	75	455	56,5	94	19	15	30	1,93	C-E-D
5030104905001600	500X1600	22	75	455	56,5	94	19	15	30	2,04	C-E-D
5030104905001800	500X1800	26	75	455	56,5	94	19	15	30	2,16	C-E-D
5030104906001200	600X1200	16	75	555	56,5	94	19	15	30	2,13	C-E-D
5030104906001400	600X1400	20	75	555	56,5	94	19	15	30	2,24	C-E-D
5030104906001600	600X1600	24	75	555	56,5	94	19	15	30	2,35	C-E-D
5030104906001800	600X1800	28	75	555	56,5	94	19	15	30	2,46	C-E-D

CONNECTIONS TYPE

SX

x

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030104904001200	495	1688	644	2197
5030104904001400	519	1770	675	2302
5030104904001600	546	1862	710	2422
5030104904001800	577	1968	751	2561
5030104905001200	646	2203	840	2865
5030104905001400	670	2285	871	2971
5030104905001600	697	2377	907	3093
5030104905001800	728	2483	947	3230
5030104906001200	799	2725	1039	3543
5030104906001400	823	2807	1070	3649
5030104906001600	850	2899	1105	3769
5030104906001800	881	3005	1146	3908

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.02	11.06	0,07	432X1330X117
9.67	11.95	0,08	432X1530X117
10.33	12.85	0,09	432X1730X117
10.98	13.73	0,10	432X1930X117
11.20	13.52	0,09	532X1330X117
11.86	14.45	0,10	532X1530X117
12.51	15.38	0,11	532X1730X117
13.17	16.30	0,13	532X1930X117
13.31	15.91	0,10	632X1330X117
13.96	16.87	0,12	632X1530X117
14.62	17.82	0,13	632X1730X117
15.27	18.79	0,15	632X1930X117

C: Central Heating / E: Electric / D: Dual Fuel