

VOGUE PLUS

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5030105105001200	500X1200	10	45	455	56,5	84,5	43	15	30	1,55	C-E-D
5030105105001400	500X1400	14	45	455	56,5	84,5	43	15	30	1,66	C-E-D
5030105105001600	500X1600	18	45	455	56,5	84,5	43	15	30	1,77	C-E-D
5030105105001800	500X1800	22	45	455	56,5	84,5	43	15	30	1,89	C-E-D


HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5030105105001200	502	1712	653	2227
5030105105001400	526	1794	684	2333
5030105105001600	553	1886	719	2452
5030105105001800	584	1992	760	2592

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
10.03	12.22	0,07	532X1330X87
10.68	13.13	0,08	532X1530X87
11.33	14.05	0,09	532X1730X87
11.99	14.96	0,09	532X1930X87

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel