

BAMBOO DOUBLE HORIZONTAL

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5040100502390800	780 x 240	2	52	745	70-96	96-122	44-70	1	119	0.36	C
5040100503590800	780 x 360	3	52	745	70-96	96-122	44-70	1	119	0.54	C-E-D
5040100504790800	780 x 480	4	52	745	70-96	96-122	44-70	1	119	0.72	C-E-D
5040100505990800	780 x 600	5	52	745	70-96	96-122	44-70	1	119	0.90	C-E-D
5040100502390900	880 x 240	2	52	845	70-96	96-122	44-70	1	119	0.39	C
5040100503590900	880 x 360	3	52	845	70-96	96-122	44-70	1	119	0.58	C-E-D
5040100504790900	880 x 480	4	52	845	70-96	96-122	44-70	1	119	0.78	C-E-D
5040100505990900	880 x 600	5	52	845	70-96	96-122	44-70	1	119	0.97	C-E-D
5040100502391000	980 x 240	2	52	945	70-96	96-122	44-70	1	119	0.42	C
5040100503591000	980 x 360	3	52	945	70-96	96-122	44-70	1	119	0.63	C-E-D
5040100504791000	980 x 480	4	52	945	70-96	96-122	44-70	1	119	0.83	C-E-D
5040100505991000	980 x 600	5	52	945	70-96	96-122	44-70	1	119	1.04	C-E-D
5040100502391100	1080 x 240	2	52	1045	70-96	96-122	44-70	1	119	0.45	C
5040100503591100	1080 x 360	3	52	1045	70-96	96-122	44-70	1	119	0.67	C-E-D
5040100504791100	1080 x 480	4	52	1045	70-96	96-122	44-70	1	119	0.89	C-E-D
5040100505991100	1080 x 600	5	52	1045	70-96	96-122	44-70	1	119	1.11	C-E-D
5040100502391200	1180 x 240	2	52	1145	70-96	96-122	44-70	1	119	0.48	C
5040100503591200	1180 x 360	3	52	1145	70-96	96-122	44-70	1	119	0.71	C-E-D
5040100504791200	1180 x 480	4	52	1145	70-96	96-122	44-70	1	119	0.95	C-E-D
5040100505991200	1180 x 600	5	52	1145	70-96	96-122	44-70	1	119	1.18	C-E-D
5040100502391300	1280 x 240	2	52	1245	70-96	96-122	44-70	1	119	0.50	C
5040100503591300	1280 x 360	3	52	1245	70-96	96-122	44-70	1	119	0.76	C-E-D
5040100504791300	1280 x 480	4	52	1245	70-96	96-122	44-70	1	119	1.01	C-E-D
5040100505991300	1280 x 600	5	52	1245	70-96	96-122	44-70	1	119	1.26	C-E-D
5040100502391400	1380 x 240	2	52	1345	70-96	96-122	44-70	1	119	0.53	C
5040100503591400	1380 x 360	3	52	1345	70-96	96-122	44-70	1	119	0.80	C-E-D
5040100504791400	1380 x 480	4	52	1345	70-96	96-122	44-70	1	119	1.06	C-E-D
5040100505991400	1380 x 600	5	52	1345	70-96	96-122	44-70	1	119	1.33	C-E-D
5040100502391500	1480 x 240	2	52	1445	70-96	96-122	44-70	1	119	0.56	C
5040100503591500	1480 x 360	3	52	1445	70-96	96-122	44-70	1	119	0.84	C-E-D
5040100504791500	1480 x 480	4	52	1445	70-96	96-122	44-70	1	119	1.12	C-E-D
5040100505991500	1480 x 600	5	52	1445	70-96	96-122	44-70	1	119	1.40	C-E-D
5040100502391600	1580 x 240	2	52	1545	70-96	96-122	44-70	1	119	0.59	C
5040100503591600	1580 x 360	3	52	1545	70-96	96-122	44-70	1	119	0.88	C-E-D
5040100504791600	1580 x 480	4	52	1545	70-96	96-122	44-70	1	119	1.18	C-E-D
5040100505991600	1580 x 600	5	52	1545	70-96	96-122	44-70	1	119	1.47	C-E-D
5040100502391700	1680 x 240	2	52	1645	70-96	96-122	44-70	1	119	0.62	C
5040100503591700	1680 x 360	3	52	1645	70-96	96-122	44-70	1	119	0.93	C-E-D
5040100504791700	1680 x 480	4	52	1645	70-96	96-122	44-70	1	119	1.23	C-E-D
5040100505991700	1680 x 600	5	52	1645	70-96	96-122	44-70	1	119	1.54	C-E-D
5040100502391800	1780 x 240	2	52	1745	70-96	96-122	44-70	1	119	0.65	C
5040100503591800	1780 x 360	3	52	1745	70-96	96-122	44-70	1	119	0.97	C-E-D
5040100504791800	1780 x 480	4	52	1745	70-96	96-122	44-70	1	119	1.29	C-E-D
5040100505991800	1780 x 600	5	52	1745	70-96	96-122	44-70	1	119	1.61	C-E-D


HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		
	mm	Watt	Btu	Watt	Btu
5040100502390800	224	763	291	992	
5040100503590800	336	1144	436	1488	
5040100504790800	448	1526	582	1984	
5040100505990800	559	1907	727	2480	
5040100502390900	246	840	320	1092	
5040100503590900	369	1260	480	1638	
5040100504790900	493	1680	640	2184	
5040100505990900	616	2100	800	2729	
5040100502391000	268	913	348	1187	
5040100503591000	402	1369	522	1780	
5040100504791000	535	1826	696	2374	
5040100505991000	669	2282	870	2967	
5040100502391100	291	993	378	1290	
5040100503591100	437	1489	568	1935	
5040100504791100	582	1985	757	2580	
5040100505991100	728	2481	946	3226	
5040100502391200	307	1048	400	1363	
5040100503591200	461	1572	599	2044	
5040100504791200	615	2096	799	2725	
5040100505991200	769	2621	999	3407	
5040100502391300	334	1140	434	1481	
5040100503591300	501	1709	652	2222	
5040100504791300	668	2279	869	2963	
5040100505991300	835	2849	1086	3704	
5040100502391400	353	1204	459	1565	
5040100503591400	529	1805	688	2347	
5040100504791400	706	2407	918	3129	
5040100505991400	882	3009	1147	3911	
5040100502391500	384	1308	499	1701	
5040100503591500	576	1963	748	2551	
5040100504791500	767	2617	998	3402	
5040100505991500	959	3271	1247	4252	
5040100502391600	405	1382	527	1796	
5040100503591600	608	2073	790	2695	
5040100504791600	810	2764	1054	3593	
5040100505991600	1013	3455	1317	4491	
5040100502391700	441	1502	573	1953	
5040100503591700	661	2253	859	2929	
5040100504791700	881	3004	1145	3906	
5040100505991700	1101	3756	1432	4882	
5040100502391800	465	1587	605	2063	
5040100503591800	698	2380	907	3094	
5040100504791800	931	3173	1210	4125	
5040100505991800	1163	3966	1512	5156	

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
4.21	5.34	0.03	890X274X87
6.31	7.65	0.04	890X394X87
8.41	9.97	0.04	890X514X87
10.52	12.30	0.05	890X634X87
4.66	5.88	0.03	990X274X87
6.99	8.45	0.04	990X394X87
9.32	11.02	0.05	990X514X87
11.65	13.59	0.06	990X634X87
5.11	6.41	0.03	1090X274X87
7.67	9.24	0.04	1090X394X87
10.22	12.04	0.05	1090X514X87
12.78	14.86	0.07	1090X634X87
5.57	6.98	0.03	1190X274X87
8.35	10.04	0.05	1190X394X87
11.13	13.10	0.06	1190X514X87
13.91	16.16	0.07	1190X634X87
6.02	7.52	0.04	1290X274X87
9.03	10.84	0.05	1290X394X87
12.04	14.15	0.06	1290X514X87
15.04	17.45	0.08	1290X634X87
6.47	8.07	0.04	1390X274X87
9.71	11.63	0.05	1390X394X87
12.94	15.18	0.07	1390X514X87
16.18	18.74	0.08	1390X634X87
6.92	8.60	0.04	1490X274X87
10.39	12.43	0.06	1490X394X87
13.85	16.23	0.07	1490X514X87
17.31	20.03	0.09	1490X634X87
7.38	9.16	0.04	1590X274X87
11.07	13.20	0.06	1590X394X87
14.75	17.26	0.08	1590X514X87
18.44	21.31	0.09	1590X634X87
7.82	9.68	0.05	1690X274X87
11.72	13.97	0.06	1690X394X87
15.63	18.27	0.08	1690X514X87
19.53	22.56	0.10	1690X634X87
8.27	10.23	0.05	1790X274X87
12.40	14.76	0.07	1790X394X87
16.53	19.31	0.09	1790X514X87
20.66	23.85	0.10	1790X634X87
8.73	10.78	0.05	1890X274X87
13.08	15.54	0.07	1890X394X87
17.44	20.34	0.09	1890X514X87
21.80	25.13	0.11	1890X634X87

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel