

BAMBOO HORIZONTAL

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5040100602390800	780 x 240	2	39	745	62-88	88-114	50-76	1	119	0,36	C
5040100603590800	780 x 360	3	39	745	62-88	88-114	50-76	1	119	0,54	C-E-D
5040100604790800	780 x 480	4	39	745	62-88	88-114	50-76	1	119	0,72	C-E-D
5040100605990800	780 x 600	5	39	745	62-88	88-114	50-76	1	119	0,90	C-E-D
5040100602390900	880 x 240	2	39	845	62-88	88-114	50-76	1	119	0,39	C
5040100603590900	880 x 360	3	39	845	62-88	88-114	50-76	1	119	0,58	C-E-D
5040100604790900	880 x 480	4	39	845	62-88	88-114	50-76	1	119	0,78	C-E-D
5040100605990900	880 x 600	5	39	845	62-88	88-114	50-76	1	119	0,97	C-E-D
5040100602391000	980 x 240	2	39	945	62-88	88-114	50-76	1	119	0,42	C
5040100603591000	980 x 360	3	39	945	62-88	88-114	50-76	1	119	0,63	C-E-D
5040100604791000	980 x 480	4	39	945	62-88	88-114	50-76	1	119	0,83	C-E-D
5040100605991000	980 x 600	5	39	945	62-88	88-114	50-76	1	119	1,04	C-E-D
5040100602391100	1080 x 240	2	39	1045	62-88	88-114	50-76	1	119	0,45	C
5040100603591100	1080 x 360	3	39	1045	62-88	88-114	50-76	1	119	0,67	C-E-D
5040100604791100	1080 x 480	4	39	1045	62-88	88-114	50-76	1	119	0,89	C-E-D
5040100605991100	1080 x 600	5	39	1045	62-88	88-114	50-76	1	119	1,11	C-E-D
5040100602391200	1180 x 240	2	39	1145	62-88	88-114	50-76	1	119	0,48	C
5040100603591200	1180 x 360	3	39	1145	62-88	88-114	50-76	1	119	0,71	C-E-D
5040100604791200	1180 x 480	4	39	1145	62-88	88-114	50-76	1	119	0,95	C-E-D
5040100605991200	1180 x 600	5	39	1145	62-88	88-114	50-76	1	119	1,18	C-E-D
5040100602391300	1280 x 240	2	39	1245	62-88	88-114	50-76	1	119	0,50	C
5040100603591300	1280 x 360	3	39	1245	62-88	88-114	50-76	1	119	0,76	C-E-D
5040100604791300	1280 x 480	4	39	1245	62-88	88-114	50-76	1	119	1,01	C-E-D
5040100605991300	1280 x 600	5	39	1245	62-88	88-114	50-76	1	119	1,26	C-E-D
5040100602391400	1380 x 240	2	39	1345	62-88	88-114	50-76	1	119	0,53	C
5040100603591400	1380 x 360	3	39	1345	62-88	88-114	50-76	1	119	0,80	C-E-D
5040100604791400	1380 x 480	4	39	1345	62-88	88-114	50-76	1	119	1,06	C-E-D
5040100605991400	1380 x 600	5	39	1345	62-88	88-114	50-76	1	119	1,33	C-E-D
5040100602391500	1480 x 240	2	39	1445	62-88	88-114	50-76	1	119	0,56	C
5040100603591500	1480 x 360	3	39	1445	62-88	88-114	50-76	1	119	0,84	C-E-D
5040100604791500	1480 x 480	4	39	1445	62-88	88-114	50-76	1	119	1,12	C-E-D
5040100605991500	1480 x 600	5	39	1445	62-88	88-114	50-76	1	119	1,40	C-E-D
5040100602391600	1580 x 240	2	39	1545	62-88	88-114	50-76	1	119	0,59	C
5040100603591600	1580 x 360	3	39	1545	62-88	88-114	50-76	1	119	0,88	C-E-D
5040100604791600	1580 x 480	4	39	1545	62-88	88-114	50-76	1	119	1,18	C-E-D
5040100605991600	1580 x 600	5	39	1545	62-88	88-114	50-76	1	119	1,47	C-E-D
5040100602391700	1680 x 240	2	39	1645	62-88	88-114	50-76	1	119	0,62	C
5040100603591700	1680 x 360	3	39	1645	62-88	88-114	50-76	1	119	0,93	C-E-D
5040100604791700	1680 x 480	4	39	1645	62-88	88-114	50-76	1	119	1,23	C-E-D
5040100605991700	1680 x 600	5	39	1645	62-88	88-114	50-76	1	119	1,54	C-E-D
5040100602391800	1780 x 240	2	39	1745	62-88	88-114	50-76	1	119	0,65	C
5040100603591800	1780 x 360	3	39	1745	62-88	88-114	50-76	1	119	0,97	C-E-D
5040100604791800	1780 x 480	4	39	1745	62-88	88-114	50-76	1	119	1,29	C-E-D
5040100605991800	1780 x 600	5	39	1745	62-88	88-114	50-76	1	119	1,61	C-E-D


HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5040100602390800	170	580	221	754
5040100603590800	255	870	332	1131
5040100604790800	340	1160	442	1508
5040100605990800	425	1450	553	1884
5040100602390900	187	638	243	830
5040100603590900	281	957	365	1245
5040100604790900	374	1276	487	1659
5040100605990900	468	1596	608	2074
5040100602391000	203	694	265	902
5040100603591000	305	1041	397	1353
5040100604791000	407	1388	529	1804
5040100605991000	509	1735	661	2255
5040100602391100	221	754	288	981
5040100603591100	332	1131	431	1471
5040100604791100	442	1509	575	1961
5040100605991100	553	1886	719	2451
5040100602391200	234	797	304	1036
5040100603591200	350	1195	456	1553
5040100604791200	467	1593	607	2071
5040100605991200	584	1992	759	2589
5040100602391300	254	866	330	1126
5040100603591300	381	1299	495	1689
5040100604791300	508	1732	660	2252
5040100605991300	635	2165	825	2815
5040100602391400	268	915	349	1189
5040100603591400	402	1372	523	1784
5040100604791400	536	1829	697	2378
5040100605991400	671	2287	872	2973
5040100602391500	292	994	379	1293
5040100603591500	437	1491	569	1939
5040100604791500	583	1989	758	2585
5040100605991500	729	2486	948	3231
5040100602391600	308	1050	400	1365
5040100603591600	462	1575	601	2048
5040100604791600	616	2100	801	2730
5040100605991600	770	2625	1001	3413
5040100602391700	335	1142	435	1484
5040100603591700	502	1712	653	2226
5040100604791700	670	2283	870	2968
5040100605991700	837	2854	1088	3710
5040100602391800	354	1206	460	1567
5040100603591800	530	1809	690	2351
5040100604791800	707	2411	919	3135
5040100605991800	884	3014	1149	3919

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
2,78	4,02	0,02	890X274X74
4,17	5,63	0,03	890X394X74
5,56	7,23	0,04	890X514X74
6,95	8,84	0,05	890X634X74
3,05	4,39	0,03	990X274X74
4,57	6,15	0,03	990X394X74
6,10	7,91	0,04	990X514X74
7,62	9,66	0,05	990X634X74
3,32	4,73	0,03	1090X274X74
4,98	6,66	0,04	1090X394X74
6,63	8,56	0,05	1090X514X74
8,29	10,48	0,06	1090X634X74
3,59	5,11	0,03	1190X274X74
5,38	7,17	0,04	1190X394X74
7,17	9,25	0,05	1190X514X74
8,96	11,32	0,06	1190X634X74
3,85	5,46	0,03	1290X274X74
5,78	7,69	0,04	1290X394X74
7,71	9,92	0,05	1290X514X74
9,63	12,14	0,07	1290X634X74
4,12	5,82	0,03	1390X274X74
6,18	8,20	0,05	1390X394X74
8,24	10,59	0,06	1390X514X74
10,31	12,97	0,07	1390X634X74
4,39	6,18	0,04	1490X274X74
6,59	8,72	0,05	1490X394X74
8,78	11,26	0,06	1490X514X74
10,98	13,80	0,07	1490X634X74
4,66	6,55	0,04	1590X274X74
6,99	9,22	0,05	1590X394X74
9,32	11,92	0,07	1590X514X74
11,65	14,61	0,08	1590X634X74
4,92	6,88	0,04	1690X274X74
7,37	9,72	0,05	1690X394X74
9,83	12,56	0,07	1690X514X74
12,28	15,40	0,08	1690X634X74
5,19	7,24	0,04	1790X274X74
7,78	10,24	0,06	1790X394X74
10,36	13,22	0,07	1790X514X74
12,95	16,23	0,09	1790X634X74
5,46	7,60	0,04	1890X274X74
8,18	10,74	0,06	1890X394X74
10,90	13,89	0,08	1890X514X74
13,62	17,04	0,09	1890X634X74

CONNECTIONS TYPE



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel