

SERO HORIZONTAL		TECHNICAL INFORMATION										(For connection types, please refer to the last page)										HEAT OUTPUTS INFORMATION				LOGISTICS INFORMATION			
MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)									
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L			Watt	Btu	Watt	Btu					kg	kg	m³	mm					
5040104302030800	840 x 200	2	29	745	57-83	72-98	44-70	3	100	0.36	C	5040104302030800	149	508	194	661	2.19	3.37	0.02	950X228X61									
5040104304090800	840 x 410	4	29	745	57-83	72-98	44-70	3	100	0.72	C-E-D	5040104304090800	298	1017	388	1322	4.38	5.93	0.03	950X434X61									
5040104306150800	840 x 620	6	29	745	57-83	72-98	44-70	3	100	1.07	C-E-D	5040104306150800	447	1525	582	1983	6.57	8.49	0.04	950X640X61									
5040104302030900	940 x 200	2	29	845	57-83	72-98	44-70	3	100	0.39	C	5040104302030900	164	560	213	728	2.38	3.62	0.02	1050X228X61									
5040104304090900	940 x 410	4	29	845	57-83	72-98	44-70	3	100	0.77	C-E-D	5040104304090900	328	1119	427	1455	4.76	6.42	0.03	1050X434X61									
5040104306150900	940 x 620	6	29	845	57-83	72-98	44-70	3	100	1.16	C-E-D	5040104306150900	492	1679	640	2183	7.14	9.21	0.05	1050X640X61									
5040104302031000	1040 x 200	2	29	945	57-83	72-98	44-70	3	100	0.42	C	5040104302031000	178	608	232	791	2.57	3.90	0.02	1150X228X61									
5040104304091000	1040 x 410	4	29	945	57-83	72-98	44-70	3	100	0.83	C-E-D	5040104304091000	357	1217	464	1582	5.14	6.91	0.04	1150X434X61									
5040104306151000	1040 x 620	6	29	945	57-83	72-98	44-70	3	100	1.24	C-E-D	5040104306151000	535	1825	696	2373	7.70	9.91	0.05	1150X640X61									
5040104302031100	1140 x 200	2	29	1045	57-83	72-98	44-70	3	100	0.45	C	5040104302031100	194	661	252	860	2.76	4.16	0.02	1250X228X61									
5040104304091100	1140 x 410	4	29	1045	57-83	72-98	44-70	3	100	0.89	C-E-D	5040104304091100	388	1323	504	1720	5.52	7.39	0.04	1250X434X61									
5040104306151100	1140 x 620	6	29	1045	57-83	72-98	44-70	3	100	1.33	C-E-D	5040104306151100	582	1984	756	2579	8.27	10.63	0.05	1250X640X61									
5040104302031200	1240 x 200	2	29	1145	57-83	72-98	44-70	3	100	0.47	C	5040104302031200	205	699	266	908	2.95	4.41	0.02	1350X228X61									
5040104304091200	1240 x 410	4	29	1145	57-83	72-98	44-70	3	100	0.94	C-E-D	5040104304091200	410	1397	533	1816	5.90	7.88	0.04	1350X434X61									
5040104306151200	1240 x 620	6	29	1145	57-83	72-98	44-70	3	100	1.41	C-E-D	5040104306151200	615	2096	799	2724	8.84	11.35	0.06	1350X640X61									
5040104302031300	1340 x 200	2	29	1245	57-83	72-98	44-70	3	100	0.50	C	5040104302031300	223	759	290	987	3.14	4.69	0.03	1450X228X61									
5040104304091300	1340 x 410	4	29	1245	57-83	72-98	44-70	3	100	1.00	C-E-D	5040104304091300	445	1519	579	1974	6.28	8.37	0.04	1450X434X61									
5040104306151300	1340 x 620	6	29	1245	57-83	72-98	44-70	3	100	1.50	C-E-D	5040104306151300	668	2278	869	2962	9.41	12.06	0.06	1450X640X61									
5040104302031400	1440 x 200	2	29	1345	57-83	72-98	44-70	3	100	0.53	C	5040104302031400	235	802	306	1043	3.33	4.94	0.03	1550X228X61									
5040104304091400	1440 x 410	4	29	1345	57-83	72-98	44-70	3	100	1.06	C-E-D	5040104304091400	470	1604	612	2085	6.66	8.87	0.05	1550X434X61									
5040104306151400	1440 x 620	6	29	1345	57-83	72-98	44-70	3	100	1.59	C-E-D	5040104306151400	706	2406	917	3128	9.98	12.78	0.07	1550X640X61									
5040104302031500	1540 x 200	2	29	1445	57-83	72-98	44-70	3	100	0.56	C	5040104302031500	256	872	332	1133	3.52	5.21	0.03	1650X228X61									
5040104304091500	1540 x 410	4	29	1445	57-83	72-98	44-70	3	100	1.12	C-E-D	5040104304091500	511	1744	665	2267	7.04	9.36	0.05	1650X434X61									
5040104306151500	1540 x 620	6	29	1445	57-83	72-98	44-70	3	100	1.67	C-E-D	5040104306151500	767	2616	997	3400	10.55	13.51	0.07	1650X640X61									
5040104302031600	1640 x 200	2	29	1545	57-83	72-98	44-70	3	100	0.59	C	5040104302031600	270	921	351	1197	3.70	5.47	0.03	1750X228X61									
5040104304091600	1640 x 410	4	29	1545	57-83	72-98	44-70	3	100	1.17	C-E-D	5040104304091600	540	1842	702	2394	7.39	9.82	0.05	1750X434X61									
5040104306151600	1640 x 620	6	29	1545	57-83	72-98	44-70	3	100	1.76	C-E-D	5040104306151600	810	2763	1053	3591	11.09	14.19	0.07	1750X640X61									
5040104302031700	1740 x 200	2	29	1645	57-83	72-98	44-70	3	100	0.62	C	5040104302031700	294	1001	382	1301	3.89	5.72	0.03	1850X228X61									
5040104304091700	1740 x 410	4	29	1645	57-83	72-98	44-70	3	100	1.23	C-E-D	5040104304091700	587	2002	763	2603	7.77	10.31	0.05	1850X434X61									
5040104306151700	1740 x 620	6	29	1645	57-83	72-98	44-70	3	100	1.84	C-E-D	5040104306151700	881	3003	1145	3904	11.66	14.90	0.08	1850X640X61									
5040104302031800	1840 x 200	2	29	1745	57-83	72-98	44-70	3	100	0.65	C	5040104302031800	310	1057	403	1374	4.08	6.00	0.03	1950X228X61									
5040104304091800	1840 x 410	4	29	1745	57-83	72-98	44-70	3	100	1.29	C-E-D	5040104304091800	620	2115	806	2749	8.15	10.81	0.06	1950X434X61									
5040104306151800	1840 x 620	6	29	1745	57-83	72-98	44-70	3	100	1.93	C-E-D	5040104306151800	930	3172	1209	4123	12.22	15.63	0.08	1950X640X61									

CONNECTIONS TYPE					
SX	ZX	YP	YL	AX	P3
✓	x	x	x	✓	✓

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel