

TECHNICAL INFORMATION												HEAT OUTPUTS INFORMATION												LOGISTICS INFORMATION			
MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type	MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C		Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)							
	mm	pieces	mm	mm	mm	mm	mm	mm	L		mm		Watt	Btu	Watt	Btu											
5040104702270800	780 x 230	4	51	745	74-100	111-137	61-87	9	50	0.58	C	5040104702270800	262	894	341	1162	3.34	4.45	0.03	890X262X86							
5040104702860800	780 x 290	5	51	745	74-100	111-137	61-87	9	50	0.72	C	5040104702860800	328	1118	426	1453	4.18	5.39	0.03	890X321X86							
5040104703450800	780 x 350	6	51	745	74-100	111-137	61-87	9	50	0.87	C-E-D	5040104703450800	393	1341	511	1743	5.01	6.33	0.03	890X380X86							
5040104704040800	780 x 400	7	51	745	74-100	111-137	61-87	9	50	1.01	C-E-D	5040104704040800	459	1565	596	2034	5.84	7.27	0.04	890X439X86							
5040104704630800	780 x 460	8	51	745	74-100	111-137	61-87	9	50	1.15	C-E-D	5040104704630800	524	1788	682	2325	6.68	8.21	0.04	890X498X86							
5040104705220800	780 x 520	9	51	745	74-100	111-137	61-87	9	50	1.30	C-E-D	5040104705220800	590	2012	767	2615	7.52	9.16	0.05	890X557X86							
5040104705810800	780 x 580	10	51	745	74-100	111-137	61-87	9	50	1.44	C-E-D	5040104705810800	655	2235	852	2906	8.36	10.11	0.05	890X616X86							
5040104706400800	780 x 640	11	51	745	74-100	111-137	61-87	9	50	1.59	C-E-D	5040104706400800	721	2459	937	3196	9.20	11.05	0.06	890X675X86							
5040104702270900	880 x 230	4	51	845	74-100	111-137	61-87	9	50	0.63	C	5040104702270900	289	984	375	1279	3.67	4.87	0.03	990X262X86							
5040104702860900	880 x 290	5	51	845	74-100	111-137	61-87	9	50	0.79	C	5040104702860900	361	1230	469	1599	4.59	5.90	0.03	990X321X86							
5040104703450900	880 x 350	6	51	845	74-100	111-137	61-87	9	50	0.95	C-E-D	5040104703450900	433	1476	563	1919	5.51	6.95	0.04	990X380X86							
5040104704040900	880 x 400	7	51	845	74-100	111-137	61-87	9	50	1.11	C-E-D	5040104704040900	505	1722	657	2239	6.43	7.98	0.04	990X439X86							
5040104704630900	880 x 460	8	51	845	74-100	111-137	61-87	9	50	1.27	C-E-D	5040104704630900	577	1968	750	2559	7.35	9.01	0.05	990X498X86							
5040104705220900	880 x 520	9	51	845	74-100	111-137	61-87	9	50	1.43	C-E-D	5040104705220900	649	2214	844	2878	8.27	10.05	0.05	990X557X86							
5040104705810900	880 x 580	10	51	845	74-100	111-137	61-87	9	50	1.59	C-E-D	5040104705810900	721	2460	938	3198	9.19	11.08	0.06	990X616X86							
5040104706400900	880 x 640	11	51	845	74-100	111-137	61-87	9	50	1.74	C-E-D	5040104706400900	794	2706	1032	3518	10.12	12.13	0.06	990X675X86							
5040104702271000	980 x 230	4	51	945	74-100	111-137	61-87	9	50	0.69	C	5040104702271000	314	1070	408	1391	4.00	5.28	0.03	1090X262X86							
5040104702861000	980 x 290	5	51	945	74-100	111-137	61-87	9	50	0.86	C	5040104702861000	392	1337	510	1738	5.01	6.42	0.04	1090X321X86							
5040104703451000	980 x 350	6	51	945	74-100	111-137	61-87	9	50	1.04	C-E-D	5040104703451000	471	1605	612	2086	6.00	7.53	0.04	1090X380X86							
5040104704041000	980 x 400	7	51	945	74-100	111-137	61-87	9	50	1.21	C-E-D	5040104704041000	549	1872	714	2434	7.01	8.68	0.05	1090X439X86							
5040104704631000	980 x 460	8	51	945	74-100	111-137	61-87	9	50	1.38	C-E-D	5040104704631000	627	2140	816	2781	8.02	9.81	0.05	1090X498X86							
5040104705221000	980 x 520	9	51	945	74-100	111-137	61-87	9	50	1.56	C-E-D	5040104705221000	706	2407	918	3129	9.02	10.94	0.06	1090X557X86							
5040104705811000	980 x 580	10	51	945	74-100	111-137	61-87	9	50	1.73	C-E-D	5040104705811000	784	2674	1020	3477	10.03	12.07	0.06	1090X616X86							
5040104706401000	980 x 640	11	51	945	74-100	111-137	61-87	9	50	1.90	C-E-D	5040104706401000	863	2942	1122	3824	11.03	13.21	0.07	1090X675X86							
5040104702271100	1080 x 230	4	51	1045	74-100	111-137	61-87	9	50	0.75	C	5040104702271100	341	1163	443	1512	4.34	5.72	0.03	1190X262X86							
5040104702861100	1080 x 290	5	51	1045	74-100	111-137	61-87	9	50	0.94	C	5040104702861100	426	1454	554	1890	5.43	6.95	0.04	1190X321X86							
5040104703451100	1080 x 350	6	51	1045	74-100	111-137	61-87	9	50	1.12	C-E-D	5040104703451100	512	1744	665	2268	6.50	8.16	0.04	1190X380X86							
5040104704041100	1080 x 400	7	51	1045	74-100	111-137	61-87	9	50	1.31	C-E-D	5040104704041100	597	2035	776	2646	7.59	9.38	0.05	1190X439X86							
5040104704631100	1080 x 460	8	51	1045	74-100	111-137	61-87	9	50	1.50	C-E-D	5040104704631100	682	2326	887	3024	8.68	10.62	0.06	1190X498X86							
5040104705221100	1080 x 520	9	51	1045	74-100	111-137	61-87	9	50	1.68	C-E-D	5040104705221100	767	2617	998	3402	9.77	11.84	0.06	1190X557X86							
5040104705811100	1080 x 580	10	51	1045	74-100	111-137	61-87	9	50	1.87	C-E-D	5040104705811100	853	2907	1108	3780	10.86	13.07	0.07	1190X616X86							
5040104706401100	1080 x 640	11	51	1045	74-100	111-137	61-87	9	50	2.06	C-E-D	5040104706401100	938	3198	1219	4158	11.95	14.31	0.07	1190X675X86							
5040104702271200	1180 x 230	4	51	1145	74-100	111-137	61-87	9	50	0.81	C	5040104702271200	360	1228	468	1597	4.67	6.14	0.03	1290X262X86							
5040104702861200	1180 x 290	5	51	1145	74-100	111-137	61-87	9	50	1.01	C	5040104702861200	450	1535	585	1996	5.84	7.45	0.04	1290X321X86							
5040104703451200	1180 x 350	6	51	1145	74-100	111-137	61-87	9	50	1.21	C-E-D	5040104703451200	540	1842	702	2395	7.00	8.77	0.05	1290X380X86							
5040104704041200	1180 x 400	7	51	1145	74-100	111-137	61-87	9	50	1.41	C-E-D	5040104704041200	630	2150	819	2794	8.18	10.09	0.05	1290X439X86							
5040104704631200	1180 x 460	8	51	1145	74-100	111-137	61-87	9	50	1.61	C-E-D	5040104704631200	720	2457	937	3194	9.35	11.42	0.06	1290X498X86							
5040104705221200	1180 x 520	9	51	1145	74-100	111-137	61-87	9	50	1.81	C-E-D	5040104705221200	810	2764	1054	3593	10.52	12.73	0.07	1290X557X86							
5040104705811200	1180 x 580	10	51	1145	74-100	111-137	61-87	9	50	2.01	C-E-D	5040104705811200	901	3071	1171	3992	11.69	14.04	0.07	1290X616X86							
5040104706401200	1180 x 640	11	51	1145	74-100	111-137	61-87	9	50	2.22	C-E-D	5040104706401200	991	3378	1288	4391	12.87	15.38	0.08	1290X675X86							
5040104702271300	1280 x 230	4	51	1245	74-100	111-137	61-87	9	50	0.86	C	5040104702271300	392	1335	509	1736	5.00	6.56	0.04	1390X262X86							
5040104702861300	1280 x 290	5	51	1245	74-100	111-137	61-87	9	50	1.08	C	5040104702861300	489	1669	636	2170	6.26	7.97	0.04	1390X321X86							
5040104703451300	1280 x 350	6	51	1245	74-100	111-137	61-87	9</																			

SIESTA HORIZONTAL

TECHNICAL INFORMATION

(For connection types, please refer to the last page)


MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5040104702861800	1780 x 290	5	51	1745	74-100	111-137	61-87	9	50	1,44	C
5040104703451800	1780 x 350	6	51	1745	74-100	111-137	61-87	9	50	1,72	C-E-D
5040104704041800	1780 x 400	7	51	1745	74-100	111-137	61-87	9	50	2,01	C-E-D
5040104704631800	1780 x 460	8	51	1745	74-100	111-137	61-87	9	50	2,30	C-E-D
5040104705221800	1780 x 520	9	51	1745	74-100	111-137	61-87	9	50	2,58	C-E-D
5040104705811800	1780 x 580	10	51	1745	74-100	111-137	61-87	9	50	2,87	C-E-D
5040104706401800	1780 x 640	11	51	1745	74-100	111-137	61-87	9	50	3,16	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
mm	Watt	Btu	Watt	Btu
5040104702861800	681	2324	886	3021
5040104703451800	818	2789	1063	3625
5040104704041800	954	3253	1240	4230
5040104704631800	1090	3718	1418	4834
5040104705221800	1227	4183	1595	5438
5040104705811800	1363	4648	1772	6042
5040104706401800	1499	5113	1949	6646

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
8,30	10,51	0,06	1890X321X86
9,97	12,38	0,07	1890X380X86
11,64	14,27	0,08	1890X439X86
13,30	16,14	0,09	1890X498X86
14,96	18,00	0,10	1890X557X86
16,62	19,88	0,11	1890X616X86
18,29	21,77	0,11	1890X675X86



SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel