

ZENO HORIZONTAL

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5040105902030800	850 x 200	2	29	745	57-83	72-98	44-70	3	100	0,36	C
5040105904090800	850 x 410	4	29	745	57-83	72-98	44-70	3	100	0,73	C-E-D
5040105906150800	850 x 620	6	29	745	57-83	72-98	44-70	3	100	1,09	C-E-D
5040105902030900	950 x 200	2	29	845	57-83	72-98	44-70	3	100	0,39	C
5040105904090900	950 x 410	4	29	845	57-83	72-98	44-70	3	100	0,78	C-E-D
5040105906150900	950 x 620	6	29	845	57-83	72-98	44-70	3	100	1,17	C-E-D
5040105902031000	1050 x 200	2	29	945	57-83	72-98	44-70	3	100	0,42	C
5040105904091000	1050 x 410	4	29	945	57-83	72-98	44-70	3	100	0,84	C-E-D
5040105906151000	1050 x 620	6	29	945	57-83	72-98	44-70	3	100	1,26	C-E-D
5040105902031100	1150 x 200	2	29	1045	57-83	72-98	44-70	3	100	0,45	C
5040105904091100	1150 x 410	4	29	1045	57-83	72-98	44-70	3	100	0,90	C-E-D
5040105906151100	1150 x 620	6	29	1045	57-83	72-98	44-70	3	100	1,34	C-E-D
5040105902031200	1250 x 200	2	29	1145	57-83	72-98	44-70	3	100	0,48	C
5040105904091200	1250 x 410	4	29	1145	57-83	72-98	44-70	3	100	0,95	C-E-D
5040105906151200	1250 x 620	6	29	1145	57-83	72-98	44-70	3	100	1,43	C-E-D
5040105902031300	1350 x 200	2	29	1245	57-83	72-98	44-70	3	100	0,51	C
5040105904091300	1350 x 410	4	29	1245	57-83	72-98	44-70	3	100	1,01	C-E-D
5040105906151300	1350 x 620	6	29	1245	57-83	72-98	44-70	3	100	1,52	C-E-D
5040105902031400	1450 x 200	2	29	1345	57-83	72-98	44-70	3	100	0,54	C
5040105904091400	1450 x 410	4	29	1345	57-83	72-98	44-70	3	100	1,07	C-E-D
5040105906151400	1450 x 620	6	29	1345	57-83	72-98	44-70	3	100	1,60	C-E-D
5040105902031500	1550 x 200	2	29	1445	57-83	72-98	44-70	3	100	0,56	C
5040105904091500	1550 x 410	4	29	1445	57-83	72-98	44-70	3	100	1,13	C-E-D
5040105906151500	1550 x 620	6	29	1445	57-83	72-98	44-70	3	100	1,69	C-E-D
5040105902031600	1650 x 200	2	29	1545	57-83	72-98	44-70	3	100	0,59	C
5040105904091600	1650 x 410	4	29	1545	57-83	72-98	44-70	3	100	1,18	C-E-D
5040105906151600	1650 x 620	6	29	1545	57-83	72-98	44-70	3	100	1,77	C-E-D
5040105902031700	1750 x 200	2	29	1645	57-83	72-98	44-70	3	100	0,62	C
5040105904091700	1750 x 410	4	29	1645	57-83	72-98	44-70	3	100	1,24	C-E-D
5040105906151700	1750 x 620	6	29	1645	57-83	72-98	44-70	3	100	1,86	C-E-D
5040105902031800	1850 x 200	2	29	1745	57-83	72-98	44-70	3	100	0,65	C
5040105904091800	1850 x 410	4	29	1745	57-83	72-98	44-70	3	100	1,30	C-E-D
5040105906151800	1850 x 620	6	29	1745	57-83	72-98	44-70	3	100	1,94	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5040105902030800	149	508	194	661
5040105904090800	298	1017	388	1322
5040105906150800	447	1525	582	1983
5040105902030900	164	560	213	728
5040105904090900	328	1119	427	1455
5040105906150900	492	1679	640	2183
5040105902031000	178	608	232	791
5040105904091000	357	1217	464	1582
5040105906151000	535	1825	696	2373
5040105902031100	194	661	252	860
5040105904091100	388	1323	504	1720
5040105906151100	582	1984	756	2579
5040105902031200	205	699	266	908
5040105904091200	410	1397	533	1816
5040105906151200	615	2096	799	2724
5040105902031300	223	759	290	987
5040105904091300	445	1519	579	1974
5040105906151300	668	2278	869	2962
5040105902031400	235	802	306	1043
5040105904091400	470	1604	612	2085
5040105906151400	706	2406	917	3128
5040105902031500	256	872	332	1133
5040105904091500	511	1744	665	2267
5040105906151500	767	2616	997	3400
5040105902031600	270	921	351	1197
5040105904091600	540	1842	702	2394
5040105906151600	810	2763	1053	3591
5040105902031700	294	1001	382	1301
5040105904091700	587	2002	763	2603
5040105906151700	881	3003	1145	3904
5040105902031800	310	1057	403	1374
5040105904091800	620	2115	806	2749
5040105906151800	930	3172	1209	4123

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (H x W x D)
kg	kg	m³	mm
2,22	3,41	0,02	970X228X61
4,45	6,02	0,03	970X434X61
6,67	8,61	0,04	970X640X61
2,41	3,67	0,02	1070X228X61
4,83	6,51	0,03	1070X434X61
7,24	9,34	0,05	1070X640X61
2,60	3,94	0,02	1170X228X61
5,21	7,00	0,04	1170X434X61
7,81	10,05	0,05	1170X640X61
2,79	4,19	0,02	1270X228X61
5,59	7,49	0,04	1270X434X61
8,38	10,76	0,05	1270X640X61
2,98	4,45	0,02	1370X228X61
5,97	7,98	0,04	1370X434X61
8,94	11,47	0,06	1370X640X61
3,17	4,73	0,03	1470X228X61
6,35	8,46	0,04	1470X434X61
9,51	12,19	0,06	1470X640X61
3,36	4,99	0,03	1570X228X61
6,73	8,97	0,05	1570X434X61
10,08	12,91	0,07	1570X640X61
3,55	5,26	0,03	1670X228X61
7,11	9,46	0,05	1670X434X61
10,65	13,64	0,07	1670X640X61
3,73	5,52	0,03	1770X228X61
7,46	9,92	0,05	1770X434X61
11,19	14,32	0,07	1770X640X61
3,92	5,77	0,03	1870X228X61
7,83	10,40	0,05	1870X434X61
11,76	15,03	0,08	1870X640X61
4,11	6,04	0,03	1970X228X61
8,21	10,89	0,06	1970X434X61
12,33	15,76	0,08	1970X640X61

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	✓	✓

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel