

ARIZZA		TECHNICAL INFORMATION (For connection types, please refer to the last page)									
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100106050965	605X965	5	47	575	37-46	74-83	24-33	15	90	1,32	C-E-D
5050100107000765	700X765	7	47	670	37-46	74-83	24-33	15	90	1,30	C-E-D
5050100106451465	645X1465	5	47	615	37-46	74-83	24-33	15	90	1,92	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100106050965	497	1695	647	2207
5050100107000765	504	1719	656	2237
5050100106451465	231	788	301	1027

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.04	10.31	0,07	652X1090X89
8.07	10.20	0,06	747X890X89
11.89	15.06	0,10	692X1590X89

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel