

ARIZZA DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100206050965	605X965	5	61	575	56-65	86-95	26-35	15	90	1,32	C-E-D
5050100207000765	700X765	7	61	670	56-65	86-95	26-35	15	90	1,30	C-E-D
5050100206451465	645X1465	5	61	615	56-65	86-95	26-35	15	90	1,92	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100206050965	632	2156	822	2804
5050100207000765	648	2210	843	2875
5050100206451465	231	788	301	1027

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
10.10	12.47	0,08	652X1090X103
10.25	12.50	0,07	747X890X103
15.51	18.74	0,12	692X1590X103

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	x	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel