

CHESTER		TECHNICAL INFORMATION (For connection types, please refer to the last page)									
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100306900765	690X765	9	101	660	69.5	120	19	15	40	1,38	C-E-D
5050100306101465	610X1465	6	101	580	69.5	120	19	15	40	2,04	C-E-D
5050100306300965	630X965	8	101	600	69.5	120	19	15	40	1,59	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100306900765	567	1934	738	2517
5050100306101465	912	3110	1186	4045
5050100306300965	745	2541	969	3305

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.64	11.91	0,10	737X890X143
13.98	17.23	0,15	657X1590X143
11.21	13.74	0,11	677X1090X143

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel