

DAIM DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100607200765	720X765	6	88	690	70-79	114-123	26-35	15	90	1,25	C-E-D
5050100605701465	570X1465	4	88	540	70-79	114-123	26-35	15	90	1,87	C-E-D
5050100605300965	530X965	4	88	500	70-79	114-123	26-35	15	90	1,27	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100607200765	598	2040	778	2653
5050100605701465	590	2012	767	2616
5050100605300965	670	2285	871	2971

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.88	12.13	0,09	767X890X130
16.41	19.44	0,13	617X1590X130
10.52	12.78	0,09	577X1090X130

CONNECTIONS TYPE

SX ✓	ZX x	YP x	YL x	AX x	P3 x
----------------------------	----------------------------	----------------------------	----------------------------	----------------------------	----------------------------

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel