

ESSINO

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100705861465	586X1465	6	36	556	56-65	106-115	26-35	15	60	2,05	C-E-D
5050100706100965	610X965	7	36	580	56-65	106-115	26-35	15	60	1,52	C-E-D
5050100707380765	738X765	9	36	708	56-65	106-115	26-35	15	60	1,46	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100705861465	225	768	293	1000
5050100706100965	683	2330	888	3029
5050100707380765	640	2183	832	2838

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
15.13	18.07	0,08	633X1590X78
11.21	13.46	0,06	657X1090X78
10.94	13.12	0,06	785X890X78

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel