

FOCHA DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050100906151465	615X1465	7	75	585	63-72	100-109	26-35	15	50	2,24	C-E-D
5050100905750965	575X965	7	75	545	63-72	100-109	26-35	15	50	1,50	C-E-D
5050100906930765	693X765	9	75	663	63-72	100-109	26-35	15	50	1,43	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050100906151465	231	788	301	1027
5050100905750965	618	2108	804	2742
5050100906930765	580	1978	754	2572

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
15.25	18.48	0,13	662X1590X117
9.98	12.31	0,08	622X1090X117
9.58	11.83	0,08	740X890X117

CONNECTIONS TYPE

SX ✓	ZX x	YP x	YL x	AX x	P3 x
----------------------------	----------------------------	----------------------------	----------------------------	----------------------------	----------------------------

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel