

HALONA

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101206500765	650X765	5	59	620	35-44	78-87	26-35	15	100	1,13	C-E-D
5050101204701465	470X1465	3	59	440	35-44	78-87	26-35	15	100	1,46	C-E-D
5050101206500965	650X965	5	59	620	35-44	78-87	26-35	15	100	1,36	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101206500765	404	1378	526	1794
5050101204701465	220	751	286	976
5050101206500965	529	1804	688	2347

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
6.95	9.02	0,07	697X890X101
8.76	11.42	0,09	517X1590X101
8.57	10.97	0,08	697X1090X101

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel