

HALONA DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101304701465	470X1465	3	88	440	70-79	114-123	26-35	15	100	1,46	C-E-D
5050101306500765	650X765	5	88	620	70-79	114-123	26-35	15	100	1,13	C-E-D
5050101306500965	650X965	5	88	620	70-79	114-123	26-35	15	100	1,36	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101304701465	220	751	286	976
5050101306500765	531	1811	691	2357
5050101306500965	707	2411	920	3138

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
11.29	14.10	0,11	517X1590X130
9.02	11.22	0,09	697X890X130
11.48	14.06	0,10	697X1090X130

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	x	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel