

LINDA		TECHNICAL INFORMATION (For connection types, please refer to the last page)									
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101406050965	605X965	5	47	575	35-44	65-74	22-31	15	90	1,32	C-E-D
5050101407000765	700X765	6	47	670	35-44	65-74	22-31	15	90	1,23	C-E-D
5050101406451465	645X1465	4	47	615	35-44	65-74	22-31	15	90	1,75	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101406050965	526	1794	684	2333
5050101407000765	470	1603	611	2084
5050101406451465	231	788	301	1027

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.94	10.21	0,07	652X1090X89
7.40	9.58	0,06	747X890X89
10.35	13.52	0,10	692X1590X89

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel