

MENTO		TECHNICAL INFORMATION (For connection types, please refer to the last page)									
MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101607260765	726X765	6	44	696	35-44	72-81	22-31	15	96	1,25	C-E-D
5050101605661465	566X1465	4	44	536	35-44	72-81	22-31	15	96	1,70	C-E-D
5050101606260965	626X965	5	44	596	35-44	72-81	22-31	15	96	1,34	C-E-D

HEAT OUTPUTS INFORMATION				
MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101607260765	487	1661	634	2162
5050101605661465	225	768	293	1000
5050101606260965	546	1862	710	2422

LOGISTICS INFORMATION			
Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.95	10.12	0,06	773X890X86
10.73	13.65	0,09	613X1590X86
8.51	10.82	0,07	673X1090X86

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel