

MENTO DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101707260765	726X765	6	62	696	57-66	88-97	26-35	15	96	1,25	C-E-D
5050101705661465	566X1465	4	62	536	57-66	88-97	26-35	15	96	1,70	C-E-D
5050101706260965	626X965	5	62	596	57-66	88-97	26-35	15	96	1,34	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101707260765	593	2023	771	2630
5050101705661465	225	768	293	1000
5050101706260965	664	2265	864	2947

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
9.16	11.46	0,08	773X890X104
12.48	15.51	0,11	613X1590X104
9.89	12.35	0,08	673X1090X104

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	x	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel