

MONA DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050101906340765	634X765	3	56	604	53-62	81-90	26-35	15	200	0,98	C-E-D
5050101906340965	634X965	3	56	604	53-62	81-90	26-35	15	200	1,15	C-E-D
5050101906741465	674X1465	3	56	644	53-62	81-90	26-35	15	200	1,61	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050101906340765	385	1313	501	1709
5050101906340965	502	1712	653	2227
5050101906741465	231	788	301	1027

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
8.71	10.79	0,06	681X890X98
11.07	13.47	0,08	681X1090X98
17.12	20.35	0,12	721X1590X98

CONNECTIONS TYPE

SX ✓	ZX x	YP x	YL x	AX x	P3 x
----------------------------	----------------------------	----------------------------	----------------------------	----------------------------	----------------------------

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel