

PERRE

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102107290765	729X765	6	39	699	69.5	95	56	15	99	1,25	C-E-D
5050102105691465	569X1465	4	39	539	69.5	95	56	15	99	1,70	C-E-D
5050102106290965	629X965	5	39	599	69.5	95	56	15	99	1,34	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102107290765	489	1668	636	2169
5050102105691465	225	768	293	1000
5050102106290965	547	1866	712	2428

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.97	10.14	0,06	776X890X81
10.79	13.68	0,08	616X1590X81
8.57	10.87	0,06	676X1090X81

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel