

PERRE DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102207290765	729X765	6	50	699	66-75	106-115	26-35	15	99	1,25	C-E-D
5050102205691465	569X1465	4	50	539	66-75	106-115	26-35	15	99	1,70	C-E-D
5050102206290965	629X965	5	50	599	66-75	106-115	26-35	15	99	1,34	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102207290765	595	2029	774	2640
5050102205691465	225	768	293	1000
5050102206290965	666	2272	866	2954

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
10.16	12.36	0,07	776X890X92
13.99	16.94	0,10	616X1590X92
11.05	13.37	0,07	676X1090X92

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	x	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel