

SALIS DOUBLE

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102505781465	578X1465	4	68	548	63-72	95-104	26-35	15	100	1,71	C-E-D
5050102507460765	746X765	6	68	716	63-72	95-104	26-35	15	100	1,26	C-E-D
5050102505380965	538X965	4	68	508	63-72	95-104	26-35	15	100	1,18	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102505781465	225	768	293	1000
5050102507460765	590	2012	767	2616
5050102505380965	533	1818	693	2364

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
12.66	15.79	0,11	625X1590X110
9.33	11.73	0,08	793X890X110
8.38	10.61	0,08	585X1090X110

CONNECTIONS TYPE

SX ✓	ZX x	YP x	YL x	AX x	P3 x
----------------------------	----------------------------	----------------------------	----------------------------	----------------------------	----------------------------

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel