

TOYA

TECHNICAL INFORMATION (For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050102906930765	693X765	9	55	663	35-44	73-82	22-31	15	50	1,43	C-E-D
5050102906151465	615X1465	7	55	585	35-44	73-82	22-31	15	50	2,24	C-E-D
5050102905750965	575X965	7	55	545	35-44	73-82	22-31	15	50	1,50	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050102906930765	552	1883	718	2449
5050102906151465	231	788	301	1027
5050102905750965	589	2009	766	2613

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
7.67	9.81	0,07	740X890X97
11.66	14.75	0,11	662X1590X97
7.89	10.11	0,07	622X1090X97

CONNECTIONS TYPE

SX	ZX	YP	YL	AX	P3
✓	x	x	x	x	x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel