

WONGA

TECHNICAL INFORMATION

(For connection types, please refer to the last page)

MODEL CODE	Width x Height (W x H)	Tube	Depth (D)	Pipe Centers (A)	Wall to Pipe Centers (L)	Depth From Wall (K)	Wall To Radiator Back (M)	Space Between Tubes (E)	Tube Width (F)	Water Volume	Fuel Type
	mm	pieces	mm	mm	mm	mm	mm	mm	mm	L	
5050103105861465	586X1465	5	60	556	56-65	86-95	26-35	15	76	1,88	C-E-D
5050103107060765	706X765	7	60	676	56-65	86-95	26-35	15	76	1,31	C-E-D
5050103106260965	626X965	6	60	596	56-65	86-95	26-35	15	76	1,44	C-E-D

HEAT OUTPUTS INFORMATION

MODEL CODE	Heat Outputs ΔT 50 °C		Heat Outputs ΔT 60 °C	
	Watt	Btu	Watt	Btu
5050103105861465	559	1907	727	2480
5050103107060765	629	2145	818	2790
5050103106260965	731	2493	951	3243

LOGISTICS INFORMATION

Net Weight	Gross Weight	Package Volume	Package Dimensions (W x H x D)
kg	kg	m³	mm
13.26	16.36	0,11	633X1590X102
9.24	11.51	0,07	753X890X102
10.18	12.59	0,08	673X1090X102

CONNECTIONS TYPE

SX

✓

ZX

x

YP

x

YL

x

AX

x

P3

x

SX, ZX, YP and YL connection types can be manufactured optionally based on customer request. Other connection types are provided as part of the standard product.

C: Central Heating / E: Electric / D: Dual Fuel